

Company Kirk et al

36-10-23E
Sec. 36 T.10 R. 23E
Loc. 330' ft WL, 800' fr. NL NW 1/4
County Wyandotte

Farm Voland

No. 1

Total Depth 600


Comm.

Comp. 6-31-31

Shot or Treated

Contractor

Issued



Elevation 923

Production 138,000 cu. ft. gas
134 # RP

Casing	
20 in.	10 in
15 1/2	8 1/4
12 1/2	6 5/8
13 3/8	5 3/16

Figures Indicate Bottom of Formation

	soil	10	shale dark	325
	sand broken	23	lime	332
	lime	37	shale	399
	shale grey	38	lime	400
	lime	39	sand	405
	shale	64	shale	407 (?)
	lime	70	red rock	408
	shale	75	sand, gas show, SLM	412
	lime	83	shale	435
	shale	125	sand	455
	lime	138	lime	459
	shale	145	shale	462
	lime	150	lime	466
	lime sandy	155	shale	472
	shale dark	160	lime	479
	shale & lime shells	171	shale	484
	lime	175	lime	485
	shale	180	shale dark	496
	lime	194	lime Lex	500
	shale	212	shale black, gas, water	502
	lime	213	lime sandy	505
	shale	215	sand SLM	510
	shale dark	225	shale	519
	lime	230	lime	522
	shale	231	shale	533
	lime	252	lime Ft. Scott	538
	shale black, wtr	255	shale	544
	lime	279	shale sandy SLM	548
	shale dark	280	shale	552
	lime	282	shale sandy	557
	shale	285	sand, gas show (good)	580
	lime SLM Hertha	293	shale blue	590
	shale	306	lime sandy	600
	sand, gas show	311		
	lime broken	315		T.D.
	shale	318		