

31-100-24E


L. M. WILLIAMS & CO.  
 Hubbard No. 1.

SEC. 31 T. 10 R. 24E  
 SW NW SE NW  
 1500' W 1820' S NW Cor.

County. Wyandotte.

Total Depth. 636 1/2'  
 Comm. 6-8-31 Comp. 6-16-31  
 Shot or Treated.  
 Contractor.  
 Issued. 8-1-36

AUG 1 1936



CASING.  
 8 1/4" 25'  
 6 5/8" 505'

Elevation.

Production. Gas Well

Figures Indicate Bottom of Formations.

soil	17	shale blue	441	SIM
lime	24	sand	445	Gas
shale	27	limo sandy	454	
lime	35	shale	486	
shale	50	lime	495	
lime	71	shale blk	497	
shale	75	lime	500	
lime	78	shale light	505	
shale	93	lime	513	
lime	123	sand	519	Gas SIM Peru 6"
shale	128	shale	530	
lime	158	lime <i>large</i>	534	
Iola 309		sand & shale	540	
shale	184	gas & wtr 2 BWP		
lime	194	lime sdy	545	
shale	204	lime	550	
lime	208	shale	562	
shale	210	lime F+ Sc. + t	565	Base Ft Scot
lime	217	shale	575	
shale	222	sand	577	- SQ - 2'
lime	232	shale	590	
shale	248	shale sdy	595	
lime	250	shale dark	597	
shale	253	shale light	599	
lime	256	sand	605	
shale	260	Dry upper Squirrel		sand
lime	289	sand broken	615	Dry 16'
shale	295	shale blue	620	
lime	314	sand hard & shells	630	
shale water	317	SIM 631 1/2'		
lime	320	sand	636 1/2'	16'
shale	324	Gas Lower Squirrel sand.		
lime	334	Total Depth	636 1/2'	
Hertha SIM 633 -				
shale	370			
sand	375	Set packer 625'		
shale grey	335			

32' SQ