15-055-21336

TRILOBITE TESTING, L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Drill-Stem Test Data

Well Name GARDEN CITY #5-2 Test No. 1 Date 8/30/94

Company OXY USA, INC. Zone MORROW

Address PO BOX 26100 OKLAHOMA CITY OK Elevation 2959

Co. Rep./Geo. CHARLES GLASCOCK Cont. BEREDCO #4 Est. Ft. of Pay

Location: Sec. 22 Twp. 23S Rge. 34W Co. FINNEY State KS

Interval Tested 4635-4730 Drill Pipe Size 4.5" XH

Anchor Length 95 Wt. Pipe I.D. - 2.7 Ft. Run

Top Packer Depth 4630-4635 Drill Collar – 2.25 Ft. Run

Bottom Packer Depth 4730 Mud Wt. lb/Gal.

Total Depth 4837 Viscosity Filtrate

Tool Open @ Initial Blow

Final Blow MADE UP TOOLS ON WALK-WHEN COMPANY GAVE ORDERS NOT TO DST-
RELOADED TOOLS-5:00 P.M.

Recovery - Total Feet Flush Tool?

Rec. Feet of

Rec. Feet of

Rec. Feet of

Rec. Feet of

Rec. Feet of

BHT °F Gravity °API @ °F Corrected Gravity °API

RW @ °F Chlorides ppm Recovery Chlorides ppm System

(A) Initial Hydrostatic Mud PSI AK1 Recorder No. 13339 Range 4025

(B) First Initial Flow Pressure PSI @ (depth) 4640 w / Clock No. 23832

(C) First Final Flow Pressure PSI AK1 Recorder No. 13276 Range 4000

(D) Initial Shut-in Pressure PSI @ (depth) 4645 w / Clock No. 17640

(E) Second Initial Flow Pressure PSI AK1 Recorder No. 13309 Range 4700

(F) Second Final Flow Pressure PSI @ (depth) 4832 w / Clock No. 23934

(G) Final Shut-in Pressure PSI Initial Opening Final Flow

(H) Final Hydrostatic Mud PSI Initial Shut-in Final Shut-in

Our Representative ROD STEINBRINK

TRILOBITE TESTING L.L.C.

P.O. Box 362 • Hays, Kansas 67601

Test Ticket

№ 7264

Well Name & No. Garden City #S-2 Test No. 1 Date 8-30-94

Company OXY USA, Inc Zone Tested Morrow

Address P.O. Box 26100 Okla. City, OK 73126-0100 Elevation 2959 (KB)

Co. Rep./Geo. Charlie Blascock Cont. Beredco #4 Est. Ft. of Pay

Location: Sec. 22 Twp. 23S Rge. 34W Co. Finney State KS

No. of Copies Distribution Sheet Yes No Turnkey Yes No Evaluation

Interval Tested 4635 - 4730 Drill Pipe Size 4½" XH

Anchor Length 95' Top Choke — 1" Bottom Choke — ¾"

Top Packer Depth 4630 - 4635 Hole Size — 7⅞" Rubber Size — 6¾"

Bottom Packer Depth 4730 Wt. Pipe I.D. — 2.7 Ft. Run —

Total Depth (LTD) 4837 Drill Collar — 2.25 Ft. Run

Mud Wt. lb/gal. Viscosity Filtrate

Tool Open @ Initial Blow Made up tools on walk

Final Blow When Company gave orders not to DST.

5:00pm Reloaded tools.

Recovery — Total Feet Feet of Gas in Pipe Flush Tool?

Rec.	Feet Of	%gas	%oil	%water	%mud
Rec.	Feet Of	%gas	%oil	%water	%mud
Rec.	Feet Of	%gas	%oil	%water	%mud
Rec.	Feet Of	%gas	%oil	%water	%mud
Rec.	Feet Of	%gas	%oil	%water	%mud

BHT °F Gravity °API @ °F Corrected Gravity °API

RW @ °F Chlorides ppm Recovery Chlorides ppm System

(A) Initial Hydrostatic Mud	PSI	AK1 Recorder No. 13339	Range 4025		
(B) First Initial Flow Pressure	PSI	@ (depth) 4640	w/Clock No. 23832		
(C) First Final Flow Pressure	PSI	AK1 Recorder No. 13276	Range 4000		
(D) Initial Shut-In Pressure	PSI	@ (depth) 4645	w/Clock No. 17640		
(E) Second Initial Flow Pressure	PSI	AK1 Recorder No. 13309	Range 4700		
(F) Second Final Flow Pressure	PSI	@ (depth) 4832	w/Clock No. 23934		
(G) Final Shut-In Pressure	PSI	Initial Opening	Test		
(H) Final Hydrostatic Mud	PSI	Initial Shut-In	Jars X		
		Final Flow	Safety Joint X		
		Final Shut-In	Straddle X		
			Circ. Sub X		
			Sampler X		
			Extra Packer X		
			Other (X) Standby 400.00		
			TOTAL PRICE $		

TRILOBITE TESTING L.L.C. SHALL NOT BE LIABLE FOR DAMAGE OF ANY KIND OF THE PROPERTY OR PERSONNEL OF THE ONE FOR WHOM A TEST IS MADE, OR FOR ANY LOSS SUFFERED OR SUSTAINED, DIRECTLY OR INDIRECTLY, THROUGH THE USE OF ITS EQUIPMENT, OR ITS STATEMENTS OR OPINION CONCERNING THE RESULTS OF ANY TEST. TOOLS LOST OR DAMAGED IN THE HOLE SHALL BE PAID FOR AT COST BY THE PARTY FOR WHOM THE TEST IS MADE.

Approved By

Our Representative Rod Steinbrink

Printcraft Printers - Hays, KS