Company- ELBUKAN OIL
Farm- Maud Clark No. 1

SEC. 31 T. 28 R. 6E
NE NE NW

Total Depth. 2906'
Comm. Comp. 4-17-22
Shot or Treated.
Contractor.
Issued.

County Butler
KANSAS

Elevation. 1382

Production. Dry

CASING:

15½"	335' P	8¼"	2395'
12½"	985' P	6 5/8	2700'
10"	1800' P		

Figures indicate Bottom of Formations

soil	8
lime	85
shale	95
lime	105
shale	115
lime	160
shale	170
red rock	180
lime	220
shale	230
lime	260
shale	290
lime	300
shale	310
lime-wtr 310-15'	330
shale	335
lime	340
shale	355
red rock	360
shale	370
lime	405
shale shelly	485
lime	500
shale	535
shale	575
red rock	585
shale	650
lime	660
shale-cave	675
slate	700
shale	720
slate	740
Enough wtr to drill 740-55	
lime	755
shale	760
shale	770
lime	775
shale	795
lime	815
shale	835
lime	860
shale	875
lime fr 875-900 watery show	
lime	930
shale	940
brwn shale	985
shale	990
lime	995
shale	1030
lime	1040
shale	1070
lime	1080
shale	1170
lime	1210
shale	1220
lime	1250
slate	1260
lime	1290
shale	1295
lime	1315
shale	1320
lime	1345
2 blr WPH 1330'	
shale	1350
lime	1380
shale	1390
lime	1435
shale	1500
lime	1530
shale	1535
lime	1540
shale	1565
lime	1585
slate-cave	1660
sand-	1680
6 Blr. WPH 1660-80	
shale	1780
lime	1790
shale	1800
shale	1805
lime	1895
5 blr WPH 1910	
wtr sand	1910
lime	2055
wtr sand	2060
lime	2085
slate-HFW	2115
shale	2215
lime	2260
lime	2295
lime	2310
slate	2312
lime	2315
shale	2340
lime	2350
slate	2355
lime	2375
shale	2395
lime	2397
shale	2410
bale hole	
shale	2440
lime	2460
shale	2465
wtr sand	2475
lime	2520
shale	2560
lime	2570
shale	2595
lime	2605
lime @ 2600, watery formation but very little wtr.	
shale	2625
shale-lime	2650
lime	2655
shale	2660
lime	2670
shale	2695
lime	2705
shale	2735
shale	2760
lime	2765
shale-show	2760 2820
lime	2825
lime	2830
shale	2835
lime -SLM	2906
Total Depth	1382
	-1524