25-14-15W


WELL LOG BUREAU -- KANSAS GEOLOGICAL SOCIETY
412 Union National Bk. Bldg., Wichita, Kansas

Company. OHIO OIL COMPANY
Farm. Harbaugh No. 9

SEC. 25 T. 14 R. 15W
SW NE NW

Total Depth. 3168 ½
Comm. 3-7-49 Comp. 3-28-49
Shot or Treated.
Contractor. Veeder Supply and DevlopmentCo.
Issued. 6-4-49

County. Russell
KANSAS



Elevation. 1763 Ind.

CASING:
8 5/8" 817' cem w/425 sx.
5 1/2" 3165' cem w/125 sx.

Production. Pumped 56.75 BO, 8 hrs.

Figures Indicate Bottom of Formations.

surface soil	40
shale, shells	120
shale lime	250
shale sand	325
shale shells sdy	375
red bed	440
shells red rock	525
red bed shale	650
red bed sand	700
red bed	740
no formation	763
red bed	1100
shale	1450
lime shells	1550
shale shells	1600
lime	2080
lime shale breaks	2165
lime	2230
lime shale brks	2350
shale shells	2450
shale, lime shells	2575
shale lime	2660
lime	2680
shale lime	2765
lime	2820
lime shale brks	2860
lime shale	2905
shale	2930
lime	3168 ½
Total Depth	

Tops:

Lansing	2923
Gorham Sand	3162

DST 2961-71, open 1 hr, rec. 15'
drilling mud. RTD 3165'.
Drilled Deeper 3167' no fluid.
3167-68½, filled up 2500' in 12 hrs.
Pumped 56.75 bbls oil in 8 hrs.
3168½ TD in Gorham sand.