

FRED DEBETZ
 Geo. W. Masterson No. 1.

SEC. 7 T. 11 R. 24E.
 SE NW SW

Total Depth. 612
 Comm. 10-4-39 Comp. 11-6-39
 Shot or Treated.
 Contractor. F. R. Pettijohn
 Issued. 4-20-40

County Wyandotte



CASING.

6" 440'

Elevation. 990 ± 20

Production. DRY.

Figures Indicate Bottom of Formations.

clay	10	sand	400
lime B.	18	oil showing 360-390	
shale B.	21	slate dark	401
lime B.	24	sand shale	440
shale L.	35	oil 438-441	
lime	36	lime sdy B.	445
shale	39	shale light	450
lime	40	lime brown	453
shale	48	shale dark	472
lime	62	lime grey	475
shale green sdy red bed and grey	85	shale grey	517
lime grey	92	lime hard	525
shale grey	95	shale dark	532
lime grey hard	102	lime dark	537
shale grey	120	slate blk	540
lime grey	148	Gas, 50 to 100,000 sand	550
shale grey	177	oil showing.	
lime	184	shale grey	555
shale	185	shale red	560
lime	187	shale Gr.	562
shale	194	lime grey sdy	577
lime grey hard	205	shale light	612
shale dark	210	Total Depth.	
lime grey hard	221	Lost tools.	
shale	235		
lime G.	237		
shale D.	238		
lime G.	240		
shale	248		
lime Br.	252		
shale D.	253		
lime Br.	270		
shale	271		
lime	274		
slate B.	276 wtr		
shale D.	280		
lime grey	300		
slate B.	303		
lime	303??		
slate and shale	305		
lime grey hard	317 Hertha.		
shale Gr.	357		