


TULSA OIL CORP.
Coffman No. 1.

SEC. 15 T. 32 R. 5 E
NW SW NW

Total Depth. 3153
Comm. 12-24-41 Comp. 2-24-42
Shot or Treated.
Contractor.
Issued. 3-28-42

County Cowley.



CASING.

85/8" 110'
5 1/2" 3069' cemented.

Elevation

Production. DRY.

Figures Indicate Bottom of Formations.

surface clay	110
lime hard	155
pyrite and sdy lime	217
lime hard	243
shale and lime	253
lime and sand	289
shale and lime	375
lime	436
red bed and shells	462
lime and green shale	565
sdv lime and little shale	588
lime and shale	610
sdv lime	647
shale and lime shells	780
shale and shells	935
sdv lime	960
shale and sdy lime	1120
sdv lime and shale	1451
shale and limeshells	1492
shale and shells	1590
shale lime and red bed	1662
lime	1765
lime and little shale	1809
sdv lime	1843
shale and lime shells	1952
sdv lime and shale	2070
lime and shale	2117
shale and lime	2185
shale and lime shells	2361
shale and shells	2441
sdv lime and shale	2491
lime and shale	2517
K.C. lime	2575
lime & strks of shale	2590
lime red and blue shale	2633
shale	2650
broken lime	2670
shale	2705
sdv lime strks of shale	2767
lime	2780
lime and shale	2825
broken lime	2924
lime and shale	3028
shale	3049
shale blue	3062
sdv shale	3085
shale	3138
shale and lime	3146
lime	3153
Total Depth.	

2924
1344

1580