


HUTCHINSON OIL & GAS CO.
Wygle No. 1.

SEC. 12 T. 27 R. 10E
NE NW SW

Total Depth. 1902' P.B.1900'
Comm. 1-10-38 Comp. 2-11-38
Shot or Treated. 1000 Gals.
Contractor. R.L.Mendenhall
Issued. 3-19-38

County. Greenwood



CASING:

12 $\frac{1}{2}$ "	425'
10 "	757'
8 $\frac{1}{4}$ "	1700'
6 "	1880'

Elevation.

Production. 12 Bbls.
20 BW

Figures Indicate Bottom of Formations.

soil	10	shale	1385
shale grey	18	lime	1395
gravel	20	shale	1410
mud yellow	30	lime	1430
lime	45	shale	1460
shale	55	lime	1470
lime	70	shale	1485
shale	80	lime	1520
lime	95	shale dk	1525
shale blue	100	lime	1530
red rock	140	shale lt	1540
shale blue	155	lime	1560
lime	170	shale	1565
shale	175	lime	1575
lime	190	shale blk	1590
shale	220	lime	1595
lime	235	sand	1610
shale	240	shale blk	1640
lime	245	shale lgt	1680
shale	275	shale	1880
4 BW 275		Mississippi lime	1880
sdv lime	300	lime	1886
shale	310	pay 1897	
lime	330	wtr sand	1902
shale	340	Total Depth.	
lime	372		
shale	380		
red rock	390	First pay 1889	
shale	395	pay to 1900	Filled up 125'
red rock	410	natural prod. 12 Bbls.	
lime	425		
shale HFW 495	465	Plugged back 2'	
lime	540		
wtr 685			
shale	740		
lime	890		
shale shells	910		
shale	1060		
lime	1075		
shale	1088		
lime	1095		
shale	1110		
lime	1255		
wtr 1265			
shale	1260		
brkn lime	1280		
shale	1305		
lime	1335		
shale	1345		
lime	1355		
shale dk	1375		
lime	1380		