


WELL LOG BUREAU KANSAS GEOLOGICAL SOCIETY  
412 Union National Bk Bldg. Wichita, Kansas

Company TANKAR GAS, INC.  
Farm Edd Forbes No. 1

SEC. 20 T. 27 R. 11E  
NE NW NW NW

Total Depth. 2452'  
Comm. 8-18-44 Comp. 10-10-44  
Shot or Treated.  
Contractor. K. T. W. #1 Star 45C W<sub>2</sub>ukesha 6  
issued. 4-3-48

County. Greenwood  
KANSAS



CASING:  
12-1/2" 555' P. 7" OD 2408' P.  
10-3/4" 1335' P. 5-1/2" 2419'  
8-5/8" 2009' P.

Elevation. \_\_\_\_\_

Production. Dry

Figures Indicate Bottom of Formations.

floor to surface	2	shale	1535
cellar	5	lime	1540
lime	10	shale	1565
shale	65	lime wh	1595
lime	75	shale wh	1615
shale	85	shale blue	1645
lime	95	lime	1650
shale	105	shale	1655
Bas Hole		lime	1680
shale	120	shale	1690
lime	125	lime	1710
shale	160	lime gy	1735
lime	190	shale blue	1755
shale	195	shale	1810
lime	205	lime	1835
shale	210	shale blk	1895
lime	220	lime	1900
shale	230	shale	1905
lime	245	red rock	1907
red rock	270	shale	1930
lime	280	shale blue	2010
red rock	295	shale lgt	2013
shale	310	lime	2015
lime	315	shale	2038
shale	325	lime gy	2041
lime	335	show oil 2041'	
shale	380	lime gy	2075
lime	390	lime blk	2175
shale	415	lime gy	2215
Fishing Job		wtr sand	2225
shale	465	lime gy	2380 SLM
lime	475	shale blk	2418
shale	490	2418 equals 2419 SLM	
lime	515	lime gy	2429
shale	540	show oil 2419 S.L.M.	
red rock	545	lime HF <sup>W</sup>	2431
lime	550	lime gy	2542
shale	580	Total Depth	
lime	595		
shale	610	TOPS:	
lime	625	K. C. lime	1185
shale	770	Miss. Lime	2038
lime	780	Arbuckle Lime	2419 SLM
shale	890		
lime	1030	1 BW 930'	
shale	1185	4 BW 940-60'	
lime K.D.	1205	2 BW 1275-1280	
shale	1210	1/2 BW 2048-51'	
lime	1225	No gas.	
red rock	1232		
lime	1300	show oil	2040-41
lime sft	1325	Show oil	2419-19 1/2
shale lime	1385	Hole straight reamed	2015-75
shale blue	1410		
shale	1475		
lime	1495		