


OKO OIL & GAS CO.
Lovett-McNeal No. 12.

SEC. 22 T. 23 R. 13E
NE SE SW

Total Depth. 1717'
Comm. 3-19-39 Comp. 5-8-39
Shot or Treated.
Contractor. Stewart & Gross
Issued. 7-15-39

County. Greenwood



CASING:
12 1/2" 623' 65/8" 1590'
10 " 844' 53/16" 1685'
8 1/4" 1424'

Elevation.

Production. Dry

Figures Indicate Bottom of Formations.

soil	10	shale HFW	1657
lime	15	lime	1660
shale	35	shale	1685
lime	45	lime	1687
shale	50	lime lgt br.	1691
lime	55	lime drk	1695
shale & shells	75	lime white	1698
shale	90	lime lgt brown	1717
lime	95	Total Depth.	
shale	110		
lime	115		
shale	130		
lime	135		
shale	200		
lime	210		
shale	225		
lime	245		
shale	255		
lime	275		
shale	315		
lime 8 BWPH	325		
shale	355		
sdv shale	400		
shale & shells	430		
lime	455		
shale	575		
lime	580		
sand HFW	585		
sdv shale	590		
lime	607		
shale blk	618		
lime	625		
shale	630		
lime	680		
shale	705		
lime	815		
sand HFW	835		
lime	850		
shale	860		
red rock	865		
shale	890		
lime	965		
shale	970		
lime	1015		
shale	1165		
lime	1170		
shale	1185		
lime	1195		
shale	1250		
lime	1255		
shale	1275		
lime	1280		
sand gas	1290		
lime 2 BWPH	1295		
shale	1305		
shale & shells	1315		
shale	1375		
sand	1380		
shale	1550		
sand(Bartlesville)wtr	1610		