GEOLOGICAL REPORT

SPUDDED 19 DEC 60 COMPLETED 29 DEC 60
COMPANY TODD E. MORGENSTERN
ADDRESS PETROLEUM GEOLOGIST
CITY & STATE KCC WICHITA
CONTRACTOR MAR-LEX OPERATIONS
ADDRESS 1000 FIDELITY BLDG.
CITY & STATE OKLAHOMA CITY, OKLA.
TYPE TOOLS ROTARY
SIZE HOLE DRILLED 7 7/8"
SIZE CASING 8 5/8" @ 220' W/ 150 SX
WT. PACKER
DEPTH OF SET
TOTAL DEPTH 3015'
DATE COMPLETED 29 DEC 60
APPROX. LOCATION NW SW SW
DRILLING TIME 60' TO 3015' 2 1/2 DAYS
ELECTRIC LOG TOPS
SAMPLE LOG
ELEVATIONS K.B. 1623' D.F. G.L.
SOURCE OF SAMPLES DRY
GEOLOGIST IN CHARGE DONALD C. TODD
FORMATION TESTS DST NO. 1 2780-2796 (OPEN 1 HR. 30 MIN. REC. 180' MUD)
DST NO. 2 2842-2879 (OPEN 1 HR. 45 MIN. REC. 192 MSW)
DST NO. 3 2877-2898 (OPEN 30 MIN. REC. 10' MUD)
DST NO. 4 2891-2910 (OPEN 1 HR. 30 MIN. REC. 229' MSW)
DST NO. 5 (RTD) 3005-3015 (OPEN 30 MIN. REC. 2' DRLG MUD)
CORES AND DRILL STEM TESTS
CASING RECORDS
REMARKS
RELEASED
FEB 2 1961
FROM CONFIDENTIAL
TODD E. MORGENSTERN
PETROLEUM GEOLOGIST
KCC WICHITA

LEGEND

Anhydrite | Salt | Sandstone | Shale | Carb sh | Limestone | Ool.Lime | Chert | Dolomite

SCALE " = 100'

SAMPLE	DEPTH	DRILLING TIME — Minutes Per Foot Rate of Penetration Decreases →	SAMPLE DESCRIPTIONS	REMARKS
	2100		LS. GRY, DX, FOSSIL, NFS IN PT	
			LS. AA.	
			SH. GRY & RD, Gummy	
			Johnson Shale? (3 GRY, FIRM, CONCH, NFS IN PT	GRANITE WASH? 2296 (-360)
			SH. GRN, Shale Cavings	
			AS ABV FOSSIL MIN, NO OIL	
	2300		LS. GRY, DX, NO SHOW OIL OR GAS	
			SH. GRY, DK, NO SHOW OIL OR GAS	
			AA. SH. LT. GRY.	
			SLTY SHY IN PART MOSTLY SH. GRN, Shale Cavings	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity	TORONTO LIME 2319 (-639)
			LS. TAN, BUFF, FOSSIL AA.	
			LS. AA. SH. GRY.	
			AS ABV, FRAGS RED SHALE Shale Cavings	
			AA SH. GRY. & GRN. MIN.	
	2400		LS. TAN, DK. GRY. FOSSIL DOL.	ELMONT 2384
			LS. GRY, TAN, AA. SH. GRY. AS ABV.	
			LS. AA. SH. GRY.	
			LS. TAN, DK. GRY. FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL.	
			SH. GRY & DK GRN.	
	2500		LS. TAN, DK. GRY. SLT.	
			SH. GRY & DK GRN.	
			SH. AA.	
			LS. TAN, DK. GRY. FOSSIL DOL. SH. & LS. AA.	
			SH. GRY & DK GRN.	HOWARD 2538 (-852)
			LS. AA.	
			LS. TAN, LT. BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	TOPEKA 2570 (-884)
	2600		LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	DST NO. 1 (TOP) 2780-2796 45-45-45-60 30" WEAK BLOW 8" IN. FLOW BLOW REC. 180' GAS MCF 1ST OPEN 1ST CLOSE
			LS. GRY, HVY GN. CHERTY FOSSIL DOL.	
			LS. GRY, HVY GN. CHERTY FOSSIL DOL.	
	2700		LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	IHP 1369 IFP 73-79 ISIP 1000 FFP 80-78 FSIP 1000 HHP 1369 TEMP 92°
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	HEEBNER 2787 (-1101)
	2800		LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	TORONTO 2817 (-1121)
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	LANSING 2831 (-1135)
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	DST NO. 2 2842-2879 45-45-45-60 30" WEAK BLOW 8" IN. FLOW BLOW REC. 192 MSW
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	IHP 1429 IFP 79-81 ISIP 1282 FFP 83-103 FSIP 1282 HHP 1429 TEMP 92°
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	DST NO. 3 2877-2898 30-30-30-30 30" WEAK BLOW DEAD IN 20 MIN. REC. 10' MUD
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	IHP 1463 IFP 10-17 ISIP 1463 FFP 17-21 FSIP 1282 HHP 1369 TEMP 92°
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	DST NO. 4 2891-2910 45-45-45-60 30" WEAK BLOW 8" IN. FLOW BLOW REC. 229' MSW
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	IHP 1498 IFP 16-98 ISIP 1282 FFP 91-118 FSIP 1282 HHP 1498 TEMP 92° CHOKE 5/8 IN. ROD
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	DST NO. 5 (RTD) 3005-3015 30-30-30-30 30" WEAK BLOW DEAD IN 20 MIN. REC. 2' DRLG MUD
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	IHP 1585 IFP 13-23 ISIP 1585 FFP 24-25 FSIP 1472 HHP 1558 TEMP 92°
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	BASE KC. 3015 (-1401)
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	DST NO. 6 (ARB) 3013-3165 30-30-30-30 30" WEAK BLOW DEAD IN 20 MIN. REC. 10' MUD
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	IHP 1628 IFP 11-16 ISIP 1472 FFP 17-17 FSIP 1390 HHP 1628 TEMP 92°
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	ARBUCKLE 3141 (-1463)
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	DST NO. 7 (ARB) 3138-3165 45-45-45-60 30" WEAK BLOW 8" IN. FLOW BLOW REC. 180' MSW
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.	IHP 1603 IFP 11-76 ISIP 1603 FFP 78-117 FSIP 1590 HHP 1603 TEMP 92°
			LS. TAN, BUFF, FOSSIL DOL.	
			LS. TAN, BUFF, FOSSIL DOL. Fair Porosity, Fair Stain & Odor, Slow Cut, Fair Fluor.