STATE: Kansas		FIELD:	
COUNTY: Sheridan		COMPANY: Continental Oil	
SEC.: 12	WELL NO.: 1	FARM: J. E. Leonard	
T.: 6	R.: 27 W	DATE COM.: 9-8-44	DATE COMPL.: 10-24-44
12		FOOTAGE LOC.: NWcor NW 330'S 330'E NW cor	
		SHOT QUARTS	BETWEEN
		ACID GALS.	BETWEEN
ALT.		CASING: 10-3/4" 240' Cem. 6" 3814' Cem.	
INIT'L. PROD.: Temp.Swb.Pot.25 B.		REMARKS	
T.D.: 3816(DFL 3814)			

"Top Lansing Lime 3608"

"TD 3814 in Lansing Lime"

TD 3816 DFL 3814

"Note: Footages calculated from pumping derrick floor level, except formations"

(OVER)

"10/12/44 Drld out com. to 3814; ran Radioactivity log; perforated 6" OD csg with Lane-Wells gun perforator from 3752 to 3759' with 24 shots; 3762 to 3770 with 36 shots; 3792 to 3798 with 12 shots; hole filled 1500' with oil in 6 hrs; swabbed 4 bbls. oil per hr. for 4 hrs.

10-15-44 Acidized through 6" OD casing with 500 gals. from 3752' to 3798'; swabbed 5 bbls. oil per hr. for 4 hrs; hole filled 1700' with oil in 10 hrs.

10-22-44 Ripped 6" OD casing from 3728' to 3739; hole filled 3400' with oil in 5 hrs.; ripped 6" OD casing from 3618'-3625'

10-24-44 Swabbed 227 bbls. oil in 5 hrs- to establish a 25 bbl. oil temporary swabbing potential "

76802.6