Kansas

Scouting Dept.

WELL RECORD.

Q.M. SHADEL Lease, Well #6.

Section 15-23-13, Greenwood County, Kansas. 190 3 feet from north line, 820 feet from west line. Drilling commenced March 21, 1924; Drilling completed April 18, 1924. Well drilled by Cosden Oil & Gas Company Tools #8.

FORMATION.	FROM	TO	REMARKS.
Soil, dark soft	0	5	
Lime, white hard	5	10	
Red Rock, Red soft	10	32	
Lime, white hard,	32	40	
Slate, light soft	40	60	
Lime, white hard	60	75	
Slate, light soft	75	85	
Lime, white hard	85	105	
Slate, light soft	105	170	
Lime, white hard	170	185	
Slate, light soft	185	240	
Lime, white hard	240	250	
Slate, light soft	250	260	
Lime, white hard	260	278	
Slate, light soft	278	295	
Lime, white hard	295	310	
Slate, light soft	310	350	
Sand, light soft	350	385	H.F.W. @ 360
Slate, light soft	385	425	Rem 12½ @ 403'
Lime, white hard	425	440	
Slate, light soft	440	465	
Lime, white hard	465	470	
Slate, light soft	470	475	
Lime, white hard	475	500	
Slate, light soft	500	595	
Lime, white hard	595	630	3 B.W. 620
Slate, black soft	630	635	
Lime, white hard	635	645	
Slate, dark soft	645	650	
Lime, white hard	650	700	
Slate, light soft	700	720	
Sand, dark soft	720	725	H.F.W. 725
Lime, white hard	725	872	
Slate, blue soft	872	878	
Lime, white hard	878	894	
Red Rock, red soft	894	904	
Sandy Lime, light hard	904	907	
Slate, blue soft	907	920	Run 10" 920
Lime, light hard	920	925	
Slate, blue soft	925	930	
Lime, white hard	930	995	5 B.W. 995
Sand, dark hard	995	1000	
Lime, white hard	1000	1020	
Slate, blue soft	1020	1023	
Lime, black hard	1023	1030	
Lime, white hard	1030	1058	
Slate, dark soft	1058	1175	
Lime, light hard	1175	1180	
Slate, light soft	1180	1185	
Lime, white hard	1185	1195	
Slate, light soft	1195	1215	
Lime, white hard	1215	1225	
Slate, light soft	1225	1270	
Lime, white hard	1270	1275	
Slate, light soft	1275	1295	
Lime, white hard	1295	1300	H.F.W. 1300

WELL RECORD .

O.M. SHADEL Lease, Well #6.

FORMATION	FROM	TO	REMARKS.
Slate, dark soft	1300	1310	Run 8¼ @ 1308
Lime,white hard	1310	1318	
Slate, blue soft	1318	1520	
Slate, black soft	1520	1541	Run 6-5/8 @ 1541
Sand, grey hard	1541	1551	
Sand ,Lay .brown soft	1551	1565	
Sand, grey med. hard	1565	1569	TOTAL.

CASING RECORD.

PUT IN			PULLED.		LEFT IN.
12½	50#	403	Pulled out	403	~~403~~
10"	40 #	920	Pulled out	920	~~920~~
8¼	24#	1308			In well
6-5/8	20#	1541			In well.