
WELL LOG BUREAU — KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

26-12-16W

Company - KEWANEE OIL CO.
Farm - Furthmeyer No. 1

SEC. 26 T. 12 R. 16W
SW SW NW
330' fr. SL, 330' fr. WL of NW/4
County. Ellis

KANSAS



Total Depth. 3545 CM
Comm. 6-11-51 Comp. 7-2-51
Shot or Treated.
Contractor.
Issued. 8-25-51

CASING:
10 3/4" 203.93 CM cem w/125 sxs.
7" 3540.33' CM cem w/125 sxs.
2 3/8" OD 3540.71 CM EUE

Elevation. ~~2063 CM~~ 2066 (Ind)

Production. State Test 1½ BOPH for 4 hrs.

Figures Indicate Bottom of Formations.

suface	0
shale	435
sand, shale	530
shale	628
sand	631
shale, sand	1034
red bed	1206
anhydrite	1245
shale, shells	1260
shale	1750
shale, shells	1950
shale, shells, lime	1975
lime, shale	1985
lime	2166
shale, lime	2187
lime	2295
lime, shale	2385
lime	2462
lime, shale	2722
shale	2820
lime, shale	2953
lime	3536
dolomite	3545 CM
Total depth	

Sample Tops CM	
Heebnershale	3220
Dodge lime	3236
Lansing, Kansas City lime	3268
Marmaton (Base KC)	3509
Arbuckle dolomite	3538

Lane Wells Tops CM:	
Heebner shale	3220
Dodge lime	3236
Lansing K. C. lime	3269
Marmaton (Base K. C.)	3508
Arbuckle dolomite	3531½