3-56

STATE: Kansas
COUNTY: Pawnee
BLOCK:
SEC.: 12
T.: 22
R.: 16W
ALTITUDE: 1992
PRODUCTION:

COMPANY: GMR
FARM: Boyd
WELL NO.: 1
SURVEY:
TOTAL DEPTH: 3927

NW-NW-NE

COMMENCED:
COMPLETED:
REMARKS: Electrolog

CASING RECORD

DST 3921-27/75, Gd 3400 MCFG/10, 60' GCM BHP 1200 #

SHOT | QUARTS | BETWEEN

FORM 186 - In stock and for sale by Ross-Martin Co., Tulsa

Samples start @ 3200

3200 gy. f-vfos. dy lst
dk. g to blk sh
c, dse
wh to g, d-f fos. dy lst
dk. g to blk sh.
3300 lt-g soft poss fos. dy lst
g, f. fos
c-bt, d-f fos. dy at base
Hbnr Sh 3396
95 blk sh
3400 HK
20 gy, f-bf to sm d-f
20 lt-g sh
36 wh to c, d-f gran, sli dy dolo. lst.
lt-g sli sdy sh
LS 3516
3500 DG Brlg LS LS
co brn sh, d-f.
16 wh to lse dy lst, sli aac por
wh to g, d-f, dy.
aac, pst, at base
dk. g to blk sh
gy-f-d-f. dy, scat aac. pst.
c-g, d-f dy. scat aac. pst.
3600
g, por, aac sli dy lst
c-bt, d-f, dy
streaks aac por. in c, dse
to f. xln. dy lst.
wh to c, d-f. scat aac. por.
3700
dk. g. sh.
g, s.f. aad aac. in part
c-g, dse.
dk. g, brnsy sh.
c, g-f sli dy. scat aac. por.
red, gy dk. g. sh
g, dse dy thin-bedded lst
3800 PBC 3833
Vi 3853
gy, dse
33 Conq
53 lt-g. sli sdy sh. & v. col. dy
Sh 3874
53 wh to dirty gray - stippled,
70 sli to sub op. frac. dull & spotty dk. oil stn.
88 micrxln earth sh
95 dk. oil stn in g. med to coarse, v to
3900 SH Miss P 20 Miss sdy sh.
Arb 3920
20 spotty oil stn in g-bf med
to co. xln vugs por.
trilobitic sli sdy. dolo.
Total Depth 3927