KANSAS WELL LOG BUREAU --- KANSAS GEOLOGICAL SOCIETY

508 EAST MURDOCK - WICHITA, KANSAS

18-26-5E

COMPANY WHITE & ELLIS CO , et al.

FARM Fry "C" NO. 1

SEC. 18 T. 26 R. 5E

LOC. CW/2 NE NE

TOTAL DEPTH 2446

COMM. 12-1-50 COMP. 12-7-50


SHOT OR TREATED

CONTRACTOR Morrison Drlg. Co., Inc.

ISSUED 6-9-51

COUNTY Butler

KANSAS



CASING

8¼" 70' cem.

4½" 2401'

ELEVATION 1345

PRODUCTION Est. 25

FIGURES INDICATE BOTTOM OF FORMATIONS

| | | | |
|---|---|---|---|
| cement | 70 | Scout Tops: | |
| broken lime | 170 | Viola | 2401 |
| lime & shale brks. | 265 | Simpson | 2424 |
| red bed | 275 | | |
| lime & shale | 320 | | |
| lime & shale strks. | 485 | | |
| shale & shells | 725 | | |
| broken lime | 795 | | |
| shale & shells | 1085 | | |
| lime & shale brks. | 1350 | | |
| lime | 1375 | | |
| shale | 1560 | | |
| lime & shale | 1615 | | |
| lime | 1645 | | |
| sandy lime | 1725 | | |
| lime | 1806 | | |
| shale & shells | 1833 | | |
| shale | 1963 | | |
| lime | 2089 | | |
| shale | 2099 | | |
| lime & shale brks. | 2137 | | |
| shale & shells | 2225 | | |
| shale & shells | 2305 | | |
| shale & lime strks. | 2314 | | |
| shale & shells | 2401 | | |
| Cable tools | | | |
| sand, coarse, some porosity & oil saturation | 2428 | | |
| 40% sand- 60% grade white chert, scattered porosity & saturation | 2430½ | | |
| cherty dolomite-slight stain of oil | 2435 | | |
| cherty dolomite-20% saturation | 2438 | | |
| cherty dolomite 65% good porosity & saturation-good show free oil (125' oil- no water in 8 Hr.) | 2442 | | |
| 80% medium porosity & oil saturation | 2444 | | |
| cherty dolomite-22% porosity & oil saturation | 2446 | | |
| Total depth | | | |

Shot 40 qts. SLG