STATE: KANSAS
COUNTY: Ellsworth
FIELD: Wildcat
PRODUCTION: 1720 BO, 330 MCF
SEC: 21
TWP: 14
RGE: 10W
LOCATION: 1715 KB
ELEVATION: 1720 DF
CONTRACTOR: Red Tiger
COMMENCED: 9-8-70
COMPLETED: 9-14-70
REMARKS: ANKY 5SC (+1179)
OPERATOR: Grove R. M. Foley
CASING RECORD: 8⅝" @ 255' / 150 sks; 4½" @ 2763' / 200 sks
SHOT / SQUEEZE / RETREAT
TIME RATE SCALE: 1/10" = 1 MINUTE
ROTARY: 450 / CABLE TOOL: / ROTARY IN O.H.
TIME DISTANCE SCALE: 1/10" = 1 MINUTE

2000
10
20
30
40
2100
10
20
30
40
50
2200
10
20
30
40
50
2300
10
20
30
40
50
2400
10
20
30
40
50
2500
10
20
30
40
50
2600
10
20
30
40
50
2700
10
20
30
40
50
2800
10
20
30
40
50
2900
10
20
30
40
50
3000

DST #1, 2102-2132
Open: 30-60-30-60
Rec: 65 in 2½ hr
30 w/m muddy w/ oil
170 sl. muddy oil
60-540 / 710-730
FP: 205"-245"

2101 (-382)
GRANDHAVEN
Heavy shale & thin ls.

Fine to medium grained gray sand, tight

DOVER LM. 2138 (-419)

TARKIO LM. 2178 (-459)

ELMONT 2243 (-524)

BURLINGAME 2319 (-600)

HOWARD 2390 (-675)

TOPEKA 2425 (-710)

WILSON CRK. 2465 (-750)

Thin ls. stringers, fossiliferous, trace of oil stain, poor porosity

DST #2, 2465-2480
Open: 60-30-30-30
Strong blow in 2min, gas to surface in 20 min
Rec: 1200' GCM
60' GIP
FP: 685"-740"

2716 (-1001)
HEEBNER

TORONTO 2732 (-1017)

2811 (-1096)
BROWN LM.

2830 (-1115)
LANSING

Heavy shale

Heavy shale

Brown cherty ls.

Good, relatively clean, fine to medium grained, sandstone, with fair to poor porosity, no show of oil or gas

DST #3, 2845-2875
Open 30-30-45-90
Strong blow, gas in 10 min
1200' GCM
60' GIP
FP: 685"-830"

Heavy shale to ls.

RTD 2970