2-54

STATE: Kansas
COUNTY: Pratt
BLOCK:
SEC. 21
T. 27 R. 11W
ALTITUDE: 1794
PRODUCTION:

COMPANY: G-M-R & Buffalo
FARM: Lion
WELL NO.: 1
SURVEY:
TOTAL DEPTH: 4515'
SE-SE-NW
COMMENCED:
COMPLETED:
REMARKS:

? CASING RECORD

DST 3500-50/1hr. 650' slt. wtr. BHP 1320#.

DST 3773-3800/1hr. 1020' GCO 60' GC. Drl. Fl. BHP 1420#.

DST 3822-35/1hr. 60' OCM, 90' OCM dy wtr. 270' s.wtr. BHP 1125#.

DST 4060-75/1hr. 40' MUD 320 BHP 0#.

SHOT QUARTS BETWEEN

FORM 186 - In stock and for sale by Ross-Martin Co., Tulsa

DST 4323-32/1hr. 30' GC Mdy wtr. BHP 0#.

R. B. STEINBERG

100 200 300 400 500 600 700 800 900 1000 1100 1200 1300 1400 1500 1600 1700 1800 1900 2000 2100 2200 2300 2400 2500 2600 2700 2800 2900 3000 3100 3200 3300 3400 3500 3600 3700 3800 3900 4000 4100 4200 4300 4400 4500 4600 4700 3800 3900 4000

Samples Start @ 3000'

gry bf f d foss

gry bf f foss

"

gry f foss

TOPEKA 3075

streaks p p por

crm gry fd streaks p p por

crm gry fd foss.

lt. gry f foss sl por ls.

crm lt gry f foss streaks p p por.

crm gry bf fd foss

gry bt f d slay

HEEBNER 3400

blk sh.

gry bt fd.

lt gry to brn fd foss

dk gry to bl/ash.

crm gry bf fd

gry fg subemicac sst

interbedded rry sh. sl por & spot dk stn. in part

lt g sdy sh.

bf to brn P. foss

LANSING 3617

gry bf to brn fd foss

gry bf fd foss scat oolic por

gry bf fd foss slay

gry bf f foss scat oolic por spot. dk stn.

crm gry bf fd slay scat oolic por

crm gry bf oolic por ls. lt oil stn

crm gry fd. scat oolic por-

crm gry bf fd scat oolic por spot. dk stn.

crm gry fd.

bf to lt brn dse

gry bf fd slay

crm gry fd

gry bf fd

" slay

crm tan dse

crm gry bf fd

tan dse

gry fd oy - pink subtrans l.a.

MISS. 4064

wh opq to subopq resid vuggy & patty lt oil stn. at top.

SKIP: 4125-75

gry bf brn f x/n ls.

KHK. SH 4200

greenish-gray & grayish-green sh. shale is dolomitic in part.

spore bearing shale -

VIOLA 4306

wh gry opq resid vuggy dolo.

gry bf med to co x/n dolo. scat vuggy por. & spot. dk stn

gry bf f x/n ay dolo. ls.

grn co x/n. to s. ls. SM 4394

grn subwaxy & l sdy sh wh to gry f to co gr. & to subrnd frosted sst. spot. blk stn.

grn subwaxy sh interbedded w/ whf. to co gr. & to subrnd frosted sl phosphatic sst

ARB 4485

gry bf f to co x/n. dolo. v. sl. sdy at top scat vuggy por.

T.D. 4515'

POOR SAMPLES

5" 4450