JERRY GREEN
CONSULTING GEOLOGIST
P.O. BOX 87
SHONEKEN, KS 67667
PHONE: 785-625-5155

GEOLOGIST'S REPORT

DRILLING TIME AND SAMPLE LOG

COMPANY Cabot Resources Inc.

LEASE Pearl Creek #2A

FIELD Basin

LOCATION 525'FNL 1525'FEL

SEC. 13 TWSP. 31S RGE. 17W

COUNTY Ellis STATE KS.

CONTRACTOR Murfin Drig Rig #24

SPUD 7-11-08 COMP.

RTD LTD

MUD UP 2600' TYPE MUD Chem.

SAMPLES SAVED FROM 2600' TO TD

DRILLING TIME KEPT FROM 2600' TO TD

SAMPLES EXAMINED FROM 2600' TO TD

GEOLOGICAL SUPERVISION FROM 2600' TO TD

GEOLOGIST ON WELL 15th-16th

ELECTRICAL SURVEYS
RAG Micro

ELEVATIONS
KB 1802
DF
GL

Measurements Are All From KB

CASING
SURFACE
PRODUCTION
LINER
TUBING

FORMATION TOPS	LOG	SAMPLE
Topeka	2706 -904	2708 -906
Heebner	2940 -1138	2940 -1138
LKC	2996 -1194	2998 -1196
BKC	3227 -1425	3227 -1425
Arbuckle	3315 -1513	3315 -1513
RTD	3401 -1599	3400 -1598

REMARKS All samples involved recommended that pipe be set on this well.

Dave Jones on site.

Verbal Submitted

LEGEND

Anhydrite | Salt | Sandstone | Shale | Carb sh | Limestone | Ool. Lime | Chert | Dolomite

DRILLING TIME IN MINUTES PER FOOT
Rate of Penetration Decreases
5" 10" 15" 20" 25"

DEPTH	LITHOLOGY	SAMPLE DESCRIPTIONS	OIL SHOWS	REMARKS
2600'				
		Lms wh-gray Fx + gray + dl sh		
		Lms offwh to tn		
2700'		Gray sh incr		
Topeka 2706 -904				
		Lt tn dol/lmst Fx M-coi Fo, Sft, P, Fair-Good Pin Foam Very Por	•	
		Lms offwh to tn Fx		
2800'		Lms tn Fx		
		Lms offwh Fx		
		Ic dl + Gray sh		
		Lms offwh to tn Fx		
2900'		Lmst lt tn Fx VM, Fo + odor	•	
Heebner 2940 -1138				
		Incr dl sh		
		Lms offwh to tn Fx		
LKC 2996 -1194				
3000'		Lms offwh Fm Fx TR odor Por.	•	
		Lms offwh TR Fo, Sft, odor	•	
		Lms offwh Fx		
3100'		Lms offwh to tn Fx TR Sft + odor Instl X-Ty Fair Por	•	
		Lms offwh to tn Fx Fo, TR Fair, Ma Foot Intbd Fair-Gd Por	•	
		Lmc offwh Fo/X Ft VM-M FO Sft Interbd SS, Ft Por	•	
		Lms offwh to tn Fx		
3200'		Lms offwh Fx TR Fo + odor Trouble zone Sft Foss Intbd Por	•	
BKC 3227 -1425				
3300'		Ic slate DE Gray Ic Green Sh		
Arbuckle 3315 -1513		Dol fm Fx to dol X Fx to vug/Fm Moder Stain Fo + Sft	•	
		Dol fm to X Chalky Mixed to Dol Fo + Sft + odor	•	
		Dol F-M-X P&M FO + Sft Interbd Por	•	
		Dol F-M-X banded Interbd Por		
RTD 3400 -1598				

DST #1
3300- 27
Blow: Strong
Zone tested: Arb
125' GMF
Rec: 225 CO
900' GWCO
55% oil
30% water
300' OCGCMW
20% oil
80% water
720' water w
a show thru
out
SIP 950-952
FP: 380-950