8-55

STATE: Kansas
COMPANY: Oil Capitol
COUNTY: Pratt
FARM: Eyers
WELL NO.: 1
BLOCK:
SURVEY:
SEC.: 28
T.: 26
R.: 11w
TOTAL DEPTH: 4481'
Sw-NE-Sw
COMMENCED:
COMPLETED:
REMARKS:
ALTITUDE:
PRODUCTION: D&A

CASING RECORD

DST 3718-46/2hrs. 100'sl. oc M. 60' sw
DST 4081-91/1hr. 15' Mud.
DST 4265-80/1hr. 30' o cm, 200' Hco, 700' w tr.

SHOT | QUARTS | BETWEEN

FORM 186 - In stock and for sale by Ross-Martin Co., Tulsa

R.B.S.

Samples Start @ 3000'

3000 grybf f foss lst-
gry f foss lst- streaks fine oolic por.
75' Top 75 gry fg sub a micac sst
gry bf fd foss lst-
TOPEKA 3075
3100 wh ltgry f foss lst.
ltgry fd scat oolic por-
3200 gry fd
gry bf f foss- slpp por
crm ltgry f foss-
tan f grn dolo. lst-
3300 crm ltgry fd foss-
ltgry soft por foss lst-
ltgry fd foss-
3400 ltgry to bf fd foss clay
30' H 30 blk sh- HEEBNER 3430
gy bf fd.
ltgry fd
crm gry fd
3500 rg sdysh
streaks of f gry fg subc micac sst.
3600 brn fd foss - ool in part
Brn 25' 25 wh crm fd foss- 45 3625
Kc
gry bf fd foss-
gry fd scat oolic por-
crm bf fd foss
3700 crm gry fd ay
crm gry bf fd foss - scat oolic por - spots dk oil stn
gry bf fd foss
gry bf fd slpp por lst
crm gry fd foss ay
3800 crm ool lic por lst-
crm ltgry fd slay streaks ool lic por-
crm fd foss slay lst-
scat ool lic por-
crm dsc
crm bf fd ay in part
dk gry to blk sh
crm gry fd
3900 bf dsc
gry bf fd ool & ool lic por
lyr part - spots lt oil stn
crm gry fd ay
bf fd ool lst- ay
gy bf fd
crm gry fd
4000 gry fd ool lst
crm gry fd ool lst
lt bf dse lst
crm gry fd ay
bf dse ay lst- Moss 4080
80' Miss 80 rg sh w/ thin beds gry dse lst.
wh opq to sub opq residual
4100 slpor w/ spots blk oil stn-
wh lt bf dse to med xln lst-
KHK SH 4144
44' Kd 44 green, gray & greenish-gray shale-
4200 streaks of gry f grn shdy dolo in part - spar bearing
62' Vio 62 Viola 4262
gry bf t med to coarse xln ay dolo-
slvuggy por & spots dk oil stn at top-
4300 gry bf f xln ay dolomitic lst.
gry bind sdy lst.
51' Simp 51 gry co xln lst- SM 4351
61' Simp Snd bf dse sdy dolomitic lst. occas subwaxy sdy sh.
gry f to coarse dolomitic sst
grn subwaxy sh interbedded
4400 w/ gry f to coarse g to sub rnd frosted & phosphatic sst.
43' Arb 43 ARB 4443'
gry bf f suc to coarse xln sl sdy dolo - oolic - scat oolic por-
4500 T.D. 4483'
3600
3700
3800
3900