

4-12-24

H. C. H. CORP.
N. Bros No. 2.

SEC. 4 T.12 R.24E
CWN NW SE

County. Johnson

Total Depth. 621'
Comm. 6-187-40 Comp. 7-1-40
Shot or Treated.
Contractor. Art Loomis
Issued. 8-3-40



CASING:

4 1/8" 392'

Elevation.

Production. Dry & Abnd.

Figures Indicate Bottom of Formations.

clay yellow	10	lime sdy	421
lime	20	shale	432
shale blue	29	lime	438
lime	46	shale, gas bubbles	455
shale	47	lime	459
lime	50-6	slate	462
shale dk	92-6	sand	470
lime	100-6	lime	472
lime	100-6	shale gy sdy	482
shale blk	104	red bed	484
lime	112	shale	488
shale dk	112	lime	491
lime	113	lime	494
shale gy	114	shale dk, slate blk	494
lime	115	shale sdy	497
shale	116	lime shaley	502
lime	120	lime	504
shale	121	shale & lime blk	507
lime	125	sand	522
slate	127	shale gy	550
shale	130	lime	551
lime	132	slate	552
shale	133	sand	558
lime	140	shale	563
shale	155	lime	568
lime	156	slate	571
shale	158	sand, gas showing	577
lime	160	lime sdy, oil showing	581
shale	163	sand	595
lime	178	shale gy sdy	596
shale	179	shale dk	599-6
lime	197	slate blk, shale blk	608
shale dk	201	lime	612
lime	222-6	slate blk	614
shale	223	sand	617
lime	223-6	shale	621
shale	226	Total Depth.	
lime	228		
shale	229		
lime, gas bubbles	230		
shale, good wtr well	232		
lime	239		
shale	249		
lime			
shale gy			
sand, gas burns in 12"			
hole	255		
sand fine & shale, wtr	260		
shale dk	275		
sand hrd	280		
shale sdy	290		
shale dk	351		
sand, gas bubbles	357		
shale gy	364		
shale dk	369		
red bed	373		
sand & shale green	375		
shale sdy gy	380		
shale red	388		
shale gy	393		
lime	395		
shale sdy green	409		
lime	415		
shale	417		