

35-13-12E

Company *Pinnacle* Pinnacle Oil & Gas Company

Sec. 35 T. 13 R. 12
Loc. NE¹

Farm E Martin

No.

Total Depth

County Wabaunsee

Comm.


Comp. July 11, 1919

Shot or Treated

Contractor

Issued

-1-



Casing

20 in. 10 in.
15 1-2 8 1-4
12 1-2 6 5-8
13 3-8 5 3-16

Elevation

Production Dry Hole

Figures Indicate Bottom of Formation

Yellow Clay	25	25
Sand	25	30
Pink Shale	30	35
Blue Shale	35	85
Gray Shale	85	100
Blue Shale	100	155
Gray Shale	135	180
Sand 5 bail. wtr.	180	185
Blue Shale	185	195
Red Rock	195	200
Blue Shale	200	280
Red Rock	280	300
Blue shale	300	350
Gray Shale	350	385
Blue Shale	385	408
Hard Lime	405	408
Blue Shale	408	425
Hard Lime	425	435
Blue Shale	435	445
Gray	445	475
D Blue Shale	475	500
Lt Gray shale	500	530
Sand 3 bail. wtr	530	560
Blue Shale	560	605
Hard Lime	605	615
Blue Shale	615	625
Lime	625	630
Gray Shale	630	700
Sand 15 bail wtr	700	715
Blue Shale	715	730
Sand-hole wtr	730	745
Blue Shale	745	800
Hard Lime	800	810
Blue Shale	810	815

Lt. Gray Shale	815	820
Hard Lime	820	840
Blue Shale Loose bldrs.	840	850
Hard Lime	850	855
B Shale	855	885
H Lime	885	905
B S ale	905	948
Lt Lime	948	950
Blue Shale	950	1020
Hard Lime	1020	1050
Black Lime	1050	1060
Gray Shale	1060	1075
Blue Shale	1075	1125
Gray Sand(hole full wtr)	1125	1130
Blue Shale water	1130	1135
Gray Sand	1135	1215
White Lime hard	1215	1220
Blue Shale	1220	1230
White Lime Hard	1230	1235
White Shale	1235	1310
Sand(hole full wtr.)	1310	1320
Hard White Lime	1320	1335
Black Slate	1335	1370
Hard Lime	1370	1400
Blue Shale	1400	1470
Hard Lime Tater	1470	1560
Blue Shale	1560	1565
White Lime 5 bail. wtr.	1565	1580
Blue shale wtr to drill	1580	1582
White Lime	1582	1600
White Lime	1600	1610
Blue Shale	1610	1665
White Lime	1665	1770
Blue Shale	1770	1775
White Lime	1775	1780
Blue Shale	1780	1800
Blue Shale	1800	1825
L Blue shale	1825	1830

P 19

1665
1670
1675

35-13-12E

Company

Sec. 35 T. 13 R. 12 E
Loc.

Farm E Martin

No.

Total Depth

County

Comm.


Comp.

Shot or Treated

Contractor

Issued

pg 2



Casing

20 in.	10 in.
15 1-2	8 1-4
12 1-2	6 5-8
13 3-8	5 3-16

Elevation

Production

Figures Indicate Bottom of Formation

Blue Shale	1830	2015	Sandy Lime	2925	2930
Gray Sand	2015	2035	Sand	2930	2945
Blue Shale	2035	2050	Lime	2945	2950
Gray Sandy Shale	2050	2065	Sandy	2950	3005
Gray Sand	2065	2090	Blue Shale	3005	3008
Black Shale	2090	2095	Lime	3008	3008
Blue Shale	2095	2200	Shad and P iron	3015	3025
Blue Shale	2200	2290	Lime & Shale	3025	3045
Hard Lime	2290	2315	Blue Shale	3045	3065
Sandy Lime	2315	2325	Sandy Lime	3065	3075
Black Shale	2325	2375	Brd Hard Lime	3075	3080
White Sand	2375	2395	Sandy Lime	3080	3100
Hard Lime	2395	2465	Brd Sand	3100	3110
Sandy Lime	2465	2528	Hard Lime	3110	3120
Black Shale	2528	2530	Sandy rust line	3120	3165
Sandy Lime	2530	2557	Sand	3165	3185
Sand	2557	2545	Hard Lime	3185	3220
Sandy Lime	2545	2637	Black Lime	3220	3300
Hard Lime	2637	2644	Hard Lime	3300	3360
Sandy Lime	2644	2650	Black Lime	3360	3440
Hard Lime	2650	2660			
Sandy Lime	2660	2670			
Hard Lime	2670	2730			
Blue Shale	2730	2745			
Dark Blue P iron	2745	2750			
L. B. Shale	2750	2885			
Lime	2885	2888			
Sand Hole full wtr	2888	2895			
Sandy Lime	2895	2925			

This well was drilled to a depth of 3640' but log has only been made up to 3440

hard as flint