

13-13-24E

COMPANY H. A. HERSEFIELD JR. et al

SEC. 13 T. 13 S. 24E  
Loc. NW SE NW

FARM Klassen

NO. 2

TOTAL DEPTH 540'

COMM. 12-7-50


COMP. 12-18-50

SHOT OR TREATED

CONTRACTOR Cullum & Brown Drlg. Co.

ISSUED 5-19-51

COUNTY Johnson



CASING

6 1/2" 423'

ELEVATION 910 ± 20  
*Length 7 1/2' Prod*

PRODUCTION 2 bbls.

FIGURES INDICATE BOTTOM OF FORMATIONS

soil sandy	11	lime	404
sand & gravel	13	shale green	413
lime	26	red bed	420
shale blue	31	shale gray	429
lime broken	35	set 6 1/4 423	
shale blue	45	shale light gray	432
lime	54	dark shale	435
shale gray	57	shale light sand	451
lime	60	lime	454
shale	61	sand	463
lime	69	reduce hole 4 7/8	
shale	99	465	
lime sandy	100	shale sandy light	475
shale dark gray	103	SLM 465	
lime	121	shale gray	489
shale	123	sand	493
lime	137	shale dark gray	499
shale gray	140	reamed to 510	
shale & slate	143	sand	500
little water		shale sandy	518
lime BF	161	sand oil	526
shale gray	163	sand broken	533
shale & slate gas		shale	540
bubbles wtr. 2 1/2		Total depth	
GPM	165		
lime broken	173	Shot 14' with 25 qts.	
SLM 165		solidified.	
lime hard (Hertha)	184		
shale dark	188		
shale light	195		
shale sandy gray	231		
lime sandy	232		
shale light sandy	244		
shale gray	293		
lime sandy	295		
sand muddy	299		
sand	310		
shale	356		
black slate	340		
shale gray	348		
lime	352		
shale	358		
lime	360		
shale	365		
lime	371		
shale dark gray	389		
lime	393		
shale & slate black	397		
water			
shale gray	399		

F-1170