

13-13-24E

COMPANY INLAND EMPIRE OIL & GAS CO. et al

SEC. 13 T. 13 R. 24E

FARM Klassen

NO. 3

LOC. SW SE NW

TOTAL DEPTH 542'

COMM. 12-29-50

COMP. 1-10-51

SHOT OR TREATED

CONTRACTOR Cullum & Brown Drlg. Co.

ISSUED 5-19-51

COUNTY Johnson

KANSAS



CASING

6" 428'

ELEVATION

PRODUCTION abandoned

FIGURES INDICATE BOTTOM OF FORMATIONS

soil & clay	14	lime	447
lime	27	shale	450
shale blue	32	lime	452
shale limey gray	42	shale (reduced hole	458
shale limey green	49	sand gas @ 459)	462
lime hard	56	lime	467
shale gray	60	sand	470
lime	70	shale light sandy	497
shale gray	99	sand	505
shale sandy dark	101	shale	511
lime	103	sand oil	515
shale limey	108	shot 510-520 20 qts.	
lime	124	shale	529
shale gray	125	sand oil	538
lime	140	shot 528-538 20 qts.	
shale	141	shale	542
shale & slate black	144	Total depth	
lime BF	168		
shale & slate black	170	Abandoned due to too heavy	
lime (Hertha)	188	shot 330' S #2	
shale dark	191		
shale green limey	205		
sand	223		
gas est. 35,000			
shale	235		
lime sandy	238		
sand	246		
shale sandy	275		
shale dark gray	298		
sand muddy	303		
sand	309		
shale sandy	347		
shale black	350		
shale gray	371		
lime	377		
shale light gray	395		
lime	400		
shale & slate black	404		
lime	410		
shale	412		
lime	415		
shale	421		
red bed	423		
dark shale	435		
SLM 428			
lime	436		
shale dark-show of			
slate	438		
shale light	444		

13-13-24E

Company Inland Empire Oil & Gas Co. et al

Sec. 13 T. 13 R. 24 E

Loc. S^W SE NW

Farm Klassen

No. 3

County Johnson

Total Depth 542

Comm. 12-29-50


Comp.

Shot or Treated

Contractor Cullem & Brown Drlg. Co.

Driller: R. A. Barnes, Tool Driller: J. Townsend

Issued



Casing

20 in.	10 in.
15 1/2	8 1/4
12 1/2	6 5/8
13 3/8	5 3/16

Elevation

Production abd.

Figures Indicate Bottom of Formation

soil and clay	14	dark shale	435	SLM 428
lime	27	lime	436	
shale blue	32	shale dark--show of slate	438	Set 6" at 428
shale limey gray	42	shale light	444	Reduced at 459' 6"
shale limey green	49			
lime hard	56	lime	447	
shale gray	60	shale	450	
lime	70	lime	452	
shale gray	99	shale	458	
shale sandy dark	101	sand	462	gas
lime	103	lime	467	
shale limey	108	sand	470	
lime	124	shale light sandy	497	
shale gray	125	sand	505	
lime	140	shale	511	
shale	141	sand	515	oil
shale & slate black	144			
lime (BF)	168	shot 510-520 20 qts.	529	
shale & slate black	170	shale	538	oil
lime (Hertha)	188	sand		
shale dark	191	shot 528-538 20 qts.	542	T.D.
shale green limey	205	shale		
sand	223			
gas est. 35,000				
shale	235			
lime sandy	238	Source of log: Driller		
sand	246	Remarks:		
shale sandy	275	Abandoned due to too heavy shot		
shale dark gray	298	330' S #2.		
sand muddy	303			
sand	309			
shale sandy	347			
shale black	350			
shale gray	371			
lime	377			
shale light gray	395			
lime	400			
shale & slate black	404	water		
lime	410			
shale	412			
lime	415			
shale	421			
red bed	423			