

Operator Name KANSAS. OIL. PROPERTIES. Lease Name WOODHEAD Well# 27 SEC. 14 TWP. 14 RGE. 20

☒ East
☐ West

WELL LOG

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all drill stem test giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface during test. Attach extra sheet if more space is needed. Attach copy of log.

Drill Stem Tests Taken

Samples Sent to Geological Survey

Cores Taken

☐ Yes ☒ No
☐ Yes ☒ No
☒ Yes ☐ No

Formation Description

☐ Log ☐ Sample

			Name	Top	Bottom
topsoil & clay	0'	20'			
river sand & gravel	20'	49'	shale	617'	631'
lime	49'	65'	lime	631'	636'
shale	65'	72'	shale	636'	659'
lime	72'	80'	lime	659'	661'
shale	80'	86'	shale	661'	665'
lime	86'	107'	sandy shale	665'	666'
shale	107'	139'			
lime	139'	160'	broken sand	666'	667'
shale	160'	220'			
lime	220'	226'	broken sand	666'	671'
shale	226'	230'	solid sand	671'	675'
lime	230'	249'	broken sand	675'	677'
shale	249'	267'	shale	667'	725'
lime	267'	275'			
shale	275'	300'			
lime	300'	306'			
shale	306'	313'			
lime	313'	314'			
shale	314'	323'			
lime	323'	249'			
shale	349'	357'			
lime	357'	381'			
shale	381'	385'			
lime	385'	399'			
shale	399'	570'			
lime	570'	575'			
shale	575'	579'			
lime	579'	584'			
shale	584'	592'			
lime	592'	598'			
shale	598'	614'			
lime	614'	617'			

CASING RECORD

☒ new☐ used

Report all strings set - conductor, surface, intermediate, production, etc.

Purpose of string	size hole drilled	size casing set (in O.D.)	weight lbs/ft.	setting depth	type of cement	# sacks used	type and percent additives
Surface Completion		6 1/4"		49'	Portland	17	2% Gel
		2 7/8ths		718.3'	" "		" "

PERFORATION RECORD

shots per foot

specify footage of each interval perforated

Acid, Fracture, Shot, Cement Squeeze Record

(amount and kind of material used)

Depth

1/9"	668'-675'		