

Pl. 15-14-22E

SPEARMAN & TRAMMEL
Bigelow No. 2.

SEC. 15 T. 14 R. 22 E
NW NE NE SW
140' NL 480' EL SW 1/2

Total Depth. 842'
Comm. 6-21-39 Comp. 7-5-39
Shot or Treated. 40 Qts. 822-39
Contractor.
Issued. 8-26-39

County. Johnson

15-14-22E



Elevation. 1016

CASING:
10" 21'
6 5/8" 814' (or 8 1/4" @ 814')

Production. 10 Bbls.

Figures Indicate Bottom of Formations.

surface	8	shale	796
sand	13	lime	798
shale	19	shale	814
lime	33	shale	820
shale	41	820 equals 818 SLM	
lime	55	sand sh oil	835 <i>BV</i>
shale	60	lime & sand	842
lime	70	Total Depth.	
shale	75		
red rock	80		
shale	92		
lime	102	Top Hertha 360, Base 369	
shale	104	Sand 822-39 sh oil in	
lime wtr	160	sand, est 12 BOPD	
shale	201		
lime	210		
shale	227		
lime	234		
shale	238		
lime	248		
shale	275		
lime	278		
shale	293		
lime	317		
shale dk	324		
lime	346		
shale	351		
lime	355		
shale	360		
lime	369		
Base Hertha 369		SLM	
shale	437		
lime	440		
shale	445		
shale blue	475		
lime & shale	480		
sand	485	<i>SSW</i>	
shale & sand	490		
shale	538		
lime	543		
shale	557		
lime	562		
shale	578		
lime sand wtr	585		
shale	589		
lime	591		
shale	594		
lime	599		
shale	602		
red rock	610		
shale	620		
lime	622		
shale	625		
lime	632		
shale	691		
lime	692		
shale	738		
ime	741		
shale	779		
me	781		

*another log
150 S. & 465 W of center*