

34-14-25E

Company Roy Lynds

Sec. 34 T. 14 R. 25E

Farm F. A. Eder

No. 5

Loc. Cen-SW

SW SW

Total Depth 697

County Johnson


Comm.

Comp.

Shot or Treated

Contractor

Issued



Elevation 1082

Casing

20 in.	10 in.
15 1/2	8 1/4
12 1/2	6 5/8
13 3/8	5 3/16

Production

Figures Indicate Bottom of Formation

soil and clay	12	dark grey shale	410
lime boulders	17	light shale	435
lime grey	62	grey shale	465
grey shale	65	dark shale	490
grey lime	80	light shale	525
white lime	95	grey lime	529
dark shale	100	light shale	535
light shale	113	red bed	542
grey lime	126	dark shale	555
grey shale	128	dark shale	560 (carried a little gas)
grey lime	132	grey shale	568
sandy lime	136	grey lime	570
red bed ⁴	145	light shale	577
grey shale	152	sand	579 ^{1/2}
grey lime	156	grey shale	590
grey shale	177	light shale	600
sand grey	187	dark shale	620
grey lime	189	sandy shale	637
grey shale	191	Oil sand	639
grey lime	205	dark sandy shale	643
grey shale	211	Oil sand	644
grey lime	241	Sand & shale	649
grey shale	249	sand	660
grey lime	251	light shale	690
black slate	253	sand	694
grey lime	255	grey shale	697
dark shale	257		
grey lime	262	Total Depth.	
grey shale	264		
grey lime	273		
black slate	277		
grey lime	278		
grey shale	279		
grey lime <u>Hertha</u>	289		
light shale	312		
sand	315		

Bart. traces of oil and little gas traces of oil