

1-15-2015

State Geological Survey
WICHITA, KANSAS

Arden Johnson Well No. W0-3

Thickness	Strata	Depth
2	Soil	2
16	Clay	18
2	Lime	20
8	Shale	28
1	Lime	29
138	Shale	167
9	Lime	176
4	Shale	180
17	Lime	197
6	Shale	203
10	Lime	213
5	Shale	218
37	Lime	255
7	Shale	262
19	Lime	281
72	Shale	353
26	Lime	379
14	Shale	393
11	Lime	404
26	Shale	430
16	Lime	446
18	Shale	464
26	Lime	490
8	Shale	498
21	Lime	519
4	Shale	523
14	Lime	537
171	Shale	708
7	Lime	715
6	Shale	721
3	Lime	724
28	Shale	752
2	Lime	754
5	Shale	759
5	Lime	764
3	Shale	767
4	Lime	771
54	Shale	825
3	Sand	828

Started Coring		
4'1"	Sand	832'1"
3'9"	Sand	835'10"
4'1"	Sand	839'11"
4'4"	Sand	844'3"
3'9"	Sand	848'0"
3'11"	Sand	851'11"
3'2"	Sand	855'1"
3'3"	Sand	858'4"

Started Drilling		
24'8"	Shale	883'0"
TD		883'0"
Plug Back Depth		868'0"

RECEIVED
STATE CORPORATION COMMISSION
FEB 19 1974
CONSERVATION DIVISION
Wichita, Kansas

