

SIDE TWO

Operator Name Painter Oil Co., Inc. Lease Name Pauline Scott Well # 1WI

Sec. 33 Twp. 15 Rge. 20 ☒ East Franklin County Franklin

METHOD OF COMPLETION

☐ Open Hole ☒ Perforation
☐ Other (Specify)

INSTRUCTIONS: Show important tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface during test. Attach extra sheet if more space is needed. Attach copy of log.

Drill Stem Tests Taken ☐ Yes ☒ No
 Samples Sent to Geological Survey ☐ Yes ☒ No
 Cores Taken ☐ Yes ☒ No

Formation Description
☐ Log ☒ Sample

	Top	Bottom
lime	408'	410'
shale	410'	424'
lime	424'	448'
shale	448'	455'
lime	455'	482'
shale	482'	485'
lime	485'	507'
shale	507'	530'
lime	530'	545'
shale	545'	566'
lime	566'	581'
shale	581'	615'
lime	615'	642'
shale	642'	672'
lime	672'	730'
sand	730'	735'
lime	735'	742'
shale	742'	770'

Name	Top	Bottom
Topsoil, clay	0	20'
shale	20'	125'
lime	125'	128'
shale	128'	137'
lime	137'	152'
shale	152'	161'
lime	161'	167'
shale	167'	171'
lime	171'	177'
shale	177'	190'
lime	190'	192'
shale	192'	217'
lime	217'	237'
shale	237'	313'
lime	313'	339'
shale	339'	351'
lime	351'	358'
shale	358'	394'
lime	394'	405'
shale	405'	408'

CASING RECORD ☒ New ☐ Used

Report all strings set-conductor, surface, intermediate, production, etc.

Purpose of String	Size Hole Drilled	Size Casing Set (in O.D.)	Weight Lbs/Ft.	Setting Depth	Type of Cement	#Sacks Used	Type and Percent Additives
surface	9 5/8"	6 1/2"		10'	portland	15	...
completion	5 5/8"	2 7/8"		700'	portland	66	...

PERFORATION RECORD

Shots Per Foot Specify Footage of Each Interval Perforated

2	710-725'

Acid, Fracture, Shot, Cement Squeeze Record

(Amount and Kind of Material Used)

Depth

TUBING RECORD Size Set At Packer at

Liner Run ☐ Yes ☐ No

Date of First Production Producing Method

☐ Flowing ☐ Pumping ☐ Gas Lift ☒ Other (explain) INJECTION WELL