

BECKEMEYER LEASE - WELL # 2
 Sec. 32, Twp. 18, Range 21
 Franklin County, Kansas.

#160 FSL
 1933 FEL
 5G SW 5G - KCC

32-15-21E

SE 1/4 160' FR 5/2 OF Sec
 11 25' FR 1/4 OF 1/4 State Geological Survey
 WICHITA, BRANCH

Thickness	Formation	Depth	Thickness	Formation	Depth
2	Top soil	2	16	Sand	550
32	Clay	34	44	Shale	594
6	Lime	40	7	Lime	601
3	Shale	43	6	Shale	607
16	Lime	59	12	Lime	619
6	Shale black	64	23	Shale	642
11	Lime	75	4	Lime	646
3	Shale	78	8	Shale	654
2	Lime	80	1	Lime	655
2	Shale	82	2	Shale	657
20	Lime	102	2	Lime	659
40	Shale	142	6	Shale	665
20	Lime	162	3	Lime	668
73	Shale	235	5	Shale black	673
22	Lime	257	10	Shale	683
25	Shale	282	2	Lime	685
9	Lime	291	5	Shale dark	690
19	Shale	309	3	Lime	693
2	Red rock	311	15	Shale	708
3	Lime	314	708-710-70 drilled 2 ft. good oil sand Started Coring- 710-70		
16	Shale	330	2.70	good oil sand	713-40
3	Lime	333	4	" " "	717-40
16	Shale	349	4.60	" " "	722
8	Lime	357	3.75	" " "	725-75
8	Shale	359	4.45	" " "	730-20
12	Lime	371	1.90	" " "	732-10
6	Shale	377	2.50	fair oil sand	734-60
27	Lime	404	1.30	oil sand laminated-poor	735-90
5	Shale	409	3.20		739-10
5	Lime	414			
3	Shale	417			
8	Lime	425			
109	Shale	534			

MAY 23 1977

RECEIVED
 STATE CORPORATION COMMISSION
 MAY 25 1976
 CONSERVATION DIVISION
 Wichita, Kansas

Top of good sand - 708-70 ft.
 Bottom of good sand - 734-60 ft.
 Drilled to T.D. of 750 ft.
 Right and left hand nipple - 558 ft. Seating nipple
 set at 708 ft. Cemented with 18 sacks of cement through
 the sand.
 This well bled extremely well and had a very clean body
 of sand.
 8 5/8" drive pipe - 36 ft.
 4.6 lb. 2" tubing set at 750 ft. and cemented with 18
 sacks of cement through the sand.

Cemented outside 2" Through 1" To surface
 10.12.1965 with 90 sacks