

SIDE TWO

ACO-1 WELL HISTORY (L)

OPERATOR Sterling Development Co INCORPORATED Robert West 13-82 SEC. 35 TWP. 15 RGE. 21 (W)

FILL IN WELL INFORMATION AS REQUIRED: WELL NO.

Show all important zones of porosity and contents thereof; cased intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION.

FORMATION DESCRIPTION, CONTENTS, ETC.	TOP	BOTTOM	NAME	DEPTH
Check if no Drill Stem Tests Run.				
soil and clay	0	9		
lime	9	19		
shale	19	27		
lime	27	39		
shale	39	45		
lime	45	63		
shale	63	98		
lime	98	118		
shale	118	198		
lime	198	241		
shale	241	248		
lime	248	254		
shale	254	308		
lime	308	334		
shale	334	342		
lime	342	371		
shale	371	375		
lime	375	384		
shale	384	545		
lime	545	551		
shale	551	584		
lime	584	589		
shale	589	606		
lime	606	610		
shale	610	660		
				710

If additional space is needed use Page 2, Side 2

Report of all strings set — surface, intermediate, production, etc. CASING RECORD (New) or (Used)

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
Surface	8 5/8	6 1/4	11 lbs	70	Portland	5	none
Production	5 1/4	2 3/8	3/75	708	Portland	90	none

LINER RECORD

PERFORATION RECORD

Top, ft.	Bottom, ft.	Sacks cement	Shots per ft.	Size & type	Depth interval
			3 / ft	1 9/16"	664.0 - 669.0
TUBING RECORD					
Size	Setting depth	Packer set at			