



OILFIELD RESEARCH LABORATORIES

536 NORTH HIGHLAND - CHANUTE, KANSAS 66720 - PHONE (316) 431-2650

April 22, 1980

Scimitar Resources Limited
104 South Silver
P.O. Box 221
Paola, Kansas 66071

Gentlemen:

Enclosed herewith is the report of the analysis of the rotary core taken from the Phlug Lease, Well No. S-3A, Miami County, Kansas, and submitted to our laboratory on March 20, 1980.

Your business is greatly appreciated.

Very truly yours,

OILFIELD RESEARCH LABORATORIES


Sanford A. Michel

SAM/tem

4 c to Paola, Kansas

Oilfield Research Laboratories

GENERAL INFORMATION & SUMMARY

Company Scimitar Resources Limited Lease Phlug ^{PFLUG} Well No. S-3A
 Location 160' SNL & 160' WEL S $\frac{1}{2}$ NW $\frac{1}{4}$
 Section 25 Twp. 16S Rge. 21E County Miami State Kansas

Elevation, Feet - - - - -

Name of Sand - - - - -	Squirrel
Top of Core - - - - -	682.0
Bottom of Core - - - - -	691.0
Top of Sand - - - - -	682.0
Bottom of Sand - - - - -	685.9
Total Feet of Permeable Sand - - - - -	3.9
Total Feet of Floodable Sand - - - - -	0.9

Distribution of Permeable Sand: Permeability Range Millidarcys	Feet	Cum. Ft.
0 - 5	2.0	2.0
10 - 20	0.9	2.9
130 - 140	1.0	3.9

Average Permeability Millidarcys - - - - -	40.1
Average Percent Porosity - - - - -	18.7
Average Percent Oil Saturation - - - - -	30.6
Average Percent Water Saturation - - - - -	52.4
Average Oil Content, Bbls./A. Ft. - - - - -	442.
Total Oil Content, Bbls./Acre - - - - -	1,724.
Average Percent Oil Recovery by Laboratory Flooding Tests - - - - -	9.0
Average Oil Recovery by Laboratory Flooding Tests, Bbls./A. Ft. - - - - -	133.
Total Oil Recovery by Laboratory Flooding Tests, Bbls./Acre - - - - -	120.
Total Calculated Oil Recovery, Bbls./Acre - - - - -	See "Calculated Recovery" Section.

-2-

The core was sampled and the samples sealed in plastic bags by a representative of the client. Fresh water mud was used as a drilling fluid. The core was reported to be from a semi-virgin area.

FORMATION CORED

The detailed log of the formation cored is as follows:

<u>Depth Interval, Feet</u>	<u>Description</u>
682.0 - 683.1	Brown shaly sandstone.
683.1 - 684.0	Light brown slightly shaly sandstone.
684.0 - 685.0	Brown slightly calcareous sandstone.
685.0 - 685.9	Grayish brown shaly sandstone.
685.9 - 691.0	Gray sandy shale.

LABORATORY FLOODING TESTS

The sand in this core responded to laboratory flooding tests, as a total recovery of 120 barrels of oil per acre was obtained from 0.9 feet of sand. The weighted average percent oil saturation was reduced from 48.0 to 39.0, or represents an average recovery of 9.0 percent. The weighted average effective permeability of the samples is 0.15 millidarcys, while the average initial fluid production pressure is 40.0 pounds per square inch (See Table V).

By observing the data given in Table IV, you will note that of the 4 samples tested, 1 produced water and oil. This indicates that approximately 25 percent of the sand represented by these samples is floodable pay sand.

-3-

CALCULATED RECOVERY

It would appear from a study of the core data, that efficient primary and waterflood operations in the vicinity of this well should recover approximately 156 barrels of oil per acre. This is an average recovery of 173 barrels per acre foot from 0.9 feet of floodable sand analyzed in this core.

These recovery values were calculated using the following data and assumptions:

Original formation volume factor, estimated	1.04
Reservoir water saturation, percent, estimated	35.0
Average porosity, percent	19.0
Oil saturation after flooding, percent	39.0
Performance factor, percent, estimated	50.0
Net floodable sand, feet	0.9

Oilfield Research Laboratories

RESULTS OF SATURATION & PERMEABILITY TESTS

TABLE 1-B

Company Scimitar Resources Limited Lease Phlug Well No. S-3A

Sample No.	Depth, Feet	Effective Porosity Percent	Percent Saturation		Oil Content Bbls. / A Ft.	Perm., Mill.	Feet of Sand		Total Oil Content	Perm. Capacity Ft. X md.
			Oil	Water			Ft.	Cum. Ft.		
1	682.5	21.7	29	63	488	4.0	1.1	1.1	537	4.40
2	683.5	19.6	16	61	243	16.	0.9	2.0	219	14.40
3	684.5	14.2	30	46	331	137.	1.0	3.0	331	137.00
4	685.5	19.0	48	38	708	0.53	0.9	3.9	637	0.48

Oilfield Research Laboratories

SUMMARY OF PERMEABILITY & SATURATION TESTS

TABLE III

Company	Lease	Well No.				
Scimitar Resources Limited	Phlug	S-3A				
Depth Interval, Feet	Feet of Core Analyzed	Average Permeability, Millidarcys	Permeability Capacity Ft. x Md.			
682.0 - 685.9	3.9	40.1	156.28			
Depth Interval, Feet	Feet of Core Analyzed	Average Percent Porosity	Average Percent Oil Saturation	Average Water Saturation	Total Oil Content Bbls./Acre	
682.0 - 685.9	3.9	18.7	30.6	52.4	442	
					1,724	

Oilfield Research Laboratories

RESULTS OF LABORATORY FLOODING TESTS

TABLE IV

Company Scimitar Resources Limited Lease Phlug Well No. S-3A

Sample No.	Depth, Feet	Effective Porosity Percent	Original Oil Saturation		Oil Recovery		Residual Saturation			Volume of Water Recovered cc*	Effective Permeability Millidarcys**	Initial Fluid Production Pressure Lbs./Sq./In.
			%	Bbls./A. Ft.	%	Bbls./A. Ft.	% Oil	% Water	Bbls./A. Ft.			
1	682.5	21.3	30	496	0	0	30	63	496	0	Imp.	-
2	683.5	20.0	15	233	0	0	15	70	233	0	Imp.	-
3	684.5	14.0	30	326	0	0	30	40	326	0	Imp.	-
4	685.5	19.0	48	708	9	133	39	55	575	10	0.15	40

Notes: cc—cubic centimeter.

*—Volume of water recovered at the time of maximum oil recovery.

**—Determined by passing water through sample which still contains residual oil.

Oilfield Research Laboratories

SUMMARY OF LABORATORY FLOODING TESTS

TABLE V

Company Scimitar Resources Limited

Lease Phlug

Well No. S-3A

Depth Interval, Feet	682.0 - 685.9
Feet of Core Analyzed	0.9
Average Percent Porosity	19.0
Average Percent Original Oil Saturation	48.0
Average Percent Oil Recovery	9.0
Average Percent Residual Oil Saturation	39.0
Average Percent Residual Water Saturation	55.0
Average Percent Total Residual Fluid Saturation	94.0
Average Original Oil Content, Bbls./A. Ft.	708.
Average Oil Recovery, Bbls./A. Ft.	133.
Average Residual Oil Content, Bbls./A. Ft.	575.
Total Original Oil Content, Bbls./Acre	638.
Total Oil Recovery, Bbls./Acre	120.
Total Residual Oil Content, Bbls./Acre	518.
Average Effective Permeability, Millidarcys	0.15
Average Initial Fluid Production Pressure, p.s.i.	40.0

NOTE: Only those samples which recovered oil were used in calculating the above averages.