

SIDE TWO

WELL LOG

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

SHOW GEOLOGICAL MARKERS, LOGS RUN, OR OTHER DESCRIPTIVE INFORMATION.

FORMATION DESCRIPTION, CONTENTS, ETC.	TOP	BOTTOM	NAME	DEPTH
soil	2	2		
clay	8	10		
lime	20	30		
shale	13	43		
lime	15	58		
shale	25	83		
lime	14	97		
shale	100	197		
lime	18	215		
shale	36	251		
lime	7	258		
shale	15	273		
lime	10	283		
shale	17	300		
lime	27	327		
shale	8	335		
lime	21	356		
shale	4	360		
lime	15	375		
shale	105	480		
sand dry	20	500		
sandy shale	40	540		
lime	8	548		
shale	7	555		
lime	3	558		
shale	24	582		
lime	4	586		
shale	17	603		
lime	4	607		
shale	12	619		
lime	4	623		
shale	12	635		
lime	5	640		
shale	16	656	Core 656-676	
shale	56	722		
lime	4	726		
shale	52	778	TD	

CONFIDENTIAL

Report of all strings set — surface, intermediate, production, etc. **CASING RECORD** ~~XXXX~~ or (Used)

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Sacks	Type and percent additives
Surface	9"	7"		21'	Portland A	5	
Production	6 1/4"	2-7/8"	6.5	741.8'	Portland A	137	5 sx 2% Prem. Gel

LINER RECORD

PERFORATION RECORD

Top, ft	Bottom, ft	Sacks cement	Shots per ft.	Size & type	Depth interval
TUBING RECORD			10/26	23 Holes = 2 per foot	2-1/8" Glass & Alum. Strip Jets 657-668
Size	Setting depth	Packer set at	12/9	23 Holes = 2 per foot	2-1/8" Alum. Strip Jets 657-668

Information within 45 days of completion, and within 30 days of completion, and within 30 days of completion, and within 30 days of completion.