

July 7, 1984

36-145-18E

es. Report all drill st
lin pressure reached
surface during test. An.

18
PGE

P1

RADER OIL COMPANY
WEBER NO.1

179	Soil & shale	179
41	Lime	220
10	Shale	250
54	Lime	284
112	Shale	396
31	Lime	427
54	Shale	481
19	Lime	500
10	Shale	510
30	Lime	540
4	Shale	544
26	Lime	570
5	Shale	575
18	Lime	593
167	Shale	760
59	Shale & shells	819
6	Lime	825
13	Shale	838
6	Lime	844
52	Shale & shells	896
8	Lime	904
48	Shale	952
6	Sandy shale	958
15	Shale	973
5	Sandy shale	978
34	Shale & shells	1,012
8	Sandy shale	1,020
180	Shale & shells	1,200
20	Sandy shale	1,220
50	Wht. sand	1,270
25	Shale	1,295
13	Lime	1,308
4	Shat	1,312
3	Lime	1,315
1	Wht. shale	1,316
28	Lime	1,344 T.D.

This well was plugged with 10 sax cement
@ 890 ft. & filled with cement from 350
ft. to surface.
Top of Miss. 1,295

RECEIVED
STATE CORPORATION COMMISSION
AUG 06 1984
CONSERVATION DIVISION
Wichita, Kansas