

SIDE TWO

Operator Name Edward E. Bink Lease Name Born Well# 3 SEC 12 TWP 19S RGE 14 ☒ East ☐ West

WELL LOG

INSTRUCTIONS: Show important tops and base of formations penetrated. Detail all cores. Report all drill stem tests giving interval tested, time tool open and closed, flowing and shut-in pressures, whether shut-in pressure reached static level, hydrostatic pressures, bottom hole temperature, fluid recovery, and flow rates if gas to surface during test. Attach extra sheet if more space is needed. Attach copy of log.

Drill Stem Tests Taken

Samples Sent to Geological Survey

Cores Taken

☐ Yes☐ Yes☒ Yes☒ No☒ No☐ No

Cones Not Tested.

22M 3 CH

Formation Description

☒ Log☐ Sample

Name	Top	Bottom
Soil - 12'	Shale - 1174'	
Shale - 28'	Lime - 1186'	
Lime - 38'	Shale - 1190'	
Shale - 42'	Lime - 1194'	
Lime - 45'	Shale - 1220'	
Shale - 147'	Lime - 1225'	
Lime - 152'	Shale - 1237'	
Shale - 224'	Lime - 1241'	
Lime - 234'	Shale - 1273'	
Shale - 240'	S. Shale - 1287'	
Lime - 263'	Lime - 1292'	
Shale - 267'	S. Shale - 1383'	
Lime - 268'	S. White - 1387'	
Shale - 272'	S. Shale - 1491'	
Lime - 285'	S. White - 1500'	
Shale - 443'	Shale - 1503'	
Lime - 447'	S. White - 1512'	
Shale - 526'		
Sand - 550'		
S. Lime - 552'		
Sand - 555'		
S. Shale - 606'		
Lime - 708'		
Shale - 797'		
Lime - 860'		
Shale - 892'		
Lime - 1005'		
Shale - 1008'		
Lime - 1015'		

CASING RECORD

☒ new☐ used

Report all strings set - conductor, surface, intermediate, production, etc.

Purpose of string	size hole drilled	size casing set (in O.D.)	weight lbs/ft.	setting depth	type of cement	# sacks used	type and percent additives
Surf. Sacs. Casing	7"			40'	Portland A.	7 sacks	

PERFORATION RECORD

shots per foot

specify footage of each interval perforated

Acid, Fracture, Shot, Cement Squeeze Record

(amount and kind of material used)

Depth
