

Plotted

12-19-2E

ALADDIN PETROLEUM CORP.  
Auguste Rempel No. 4

SEC. 12 T. 19 R. 2E.  
SW SE SE

Total Depth. 2857 $\frac{1}{2}$   
Compt. 7-18-40 Comp. 8-7-40  
Shot or Treated.  
Contractor. Hannum Drilling Co.  
Issued. 10-12-40

County Marion.



CASING.

13" 133' 5 $\frac{1}{2}$ " 2851'

Elevation.

Production. 65 B. Oil  
25 bbls wtr.

Figures Indicate Bottom of Formations.

surface	30	limo	1685
shale and shells	190	shale and shells	1840
lime shells and shale	260	sand	1895
shale	275	broken limo	1925
shale and shells	325	limo	2035
sdv line	331	broken limo	2110
lime and shale	436	limo	2200
sdv line	456	broken limo	2280
shale and lime shells	530	lime	2305
lime and shale	562	broken limo	2325
sdv line	605	limo	2335
lime and red rock	625	broken limo	2365
lime	660	broken limo & shale	2469 $\frac{1}{2}$
shale	675	chat	2553
sdv line shale	700	chat and limo	2580
shale and shells	760	limo	2616
sdv lime and shale	825	shale	2730
shale and shells	975	shale grey	2851
sand	1005	dolomite	2857 $\frac{1}{2}$
shale	1080	Total Depth.	
lime	1090		
shale and shells	1110	Top Miss. (D.F.M.)	2468
lime and shale	1145	Top Viola	2851
shale and shells	1165		
sdv lime	1200		
shale	1245		
shale and shells	1335	Cored	2851-57 $\frac{1}{2}$
limo	1365	3 $\frac{1}{2}$ ' Recovery.	
shale and shells	1422	Sat. dolomite	
lime	1445		
shale	1480		
sdv lime	1530		
lime	1550		
lime and shale	1600		
shale and shells	1650		