

P1  
TYPE

AFFIDAVIT OF COMPLETION FORM

ACO-1 WELL HISTORY

Compt. \_\_\_\_\_

SIDE ONE

(Rules 82-3-130 and 82-3-107)

DOCKET NO. NP \_\_\_\_\_

This form shall be filed with the Kansas Corporation Commission, 200 Colorado Derby Building, Wichita, Kansas 67202, within ninety (90) days after the completion of a well, regardless of how the well was completed.

FOR INFORMATION REGARDING THE NUMBER OF COPIES TO BE FILED AND APPLICATIONS REQUIRING COPIES OF ACO-1 FORMS SEE PAGE TWO (2), SIDE TWO (2) OF THIS FORM.

F \_\_\_\_\_ Letter requesting confidentiality attached.

C \_\_\_\_\_ Attach ONE COPY of EACH wireline log run (i.e. electrical log, sonic log, gamma ray neutron log etc.)\*\*\*Check here if NO logs were run \_\_\_\_\_.

PLEASE FILL IN ALL INFORMATION. IF NOT AVAILABLE, INDICATE. IF INFORMATION LATER BECOMES AVAILABLE, SUBMIT BY LETTER.

LICENSE # 6515 EXPIRATION DATE \_\_\_\_\_

OPERATOR The Dallas Group, Inc. API NO. 15-201-20,002

ADDRESS 18601 LBJ Freeway, Suite 660 COUNTY Washington

Mesquite, Texas 75150 FIELD \_\_\_\_\_

\*\* CONTACT PERSON Bob Stanley PROD. FORMATION \_\_\_\_\_  
PHONE 214-681-8346 \_\_\_\_\_ Indicate if new pay.

PURCHASER \_\_\_\_\_ LEASE Rift #1-83 Ltd.

ADDRESS \_\_\_\_\_ WELL NO. 33

DRILLING Brandt Drilling Co., Inc. 1650 Ft. from North Line and

CONTRACTOR 1200 Douglas Building 2310 Ft. from West Line of (E)

ADDRESS Wichita, Kansas 67202 the NW (Qtr.) SEC 8 TWP 1 SRGE 1 ~~1~~ ~~1~~

PLUGGING Brandt Drilling Co., Inc. WELL PLAT \_\_\_\_\_ (Office

CONTRACTOR \_\_\_\_\_ Use Only)

ADDRESS 1200 Douglas Building KCC \_\_\_\_\_

Wichita, Kansas 67202 KGS

TOTAL DEPTH 3445' PBTD \_\_\_\_\_ SWD/REP \_\_\_\_\_

SPUD DATE 11-21-83 DATE COMPLETED 12-1-83 PLG. \_\_\_\_\_

ELEV: GR 1600' DF \_\_\_\_\_ KB \_\_\_\_\_ NGPA \_\_\_\_\_

DRILLED WITH (CABLE) / (ROTARY) / (AIR) TOOLS.

DOCKET NO. OF DISPOSAL OR REPRESSURING WELL BEING USED TO DISPOSE OF WATER FROM THIS LEASE \_\_\_\_\_

Amount of surface pipe set and cemented 328' DV Tool Used? No

TYPE OF COMPLETION THIS AFFIDAVIT APPLIES TO: (Circle ONE) - Oil, Shut-in Gas, Gas, Dry, Disposal, Injection, Temporarily Abandoned. If OWWO, indicate type of re-completion \_\_\_\_\_. Other completion \_\_\_\_\_. NGPA filing \_\_\_\_\_

ALL REQUIREMENTS OF THE STATUTES, RULES AND REGULATIONS PROMULGATED TO REGULATE THE OIL AND GAS INDUSTRY HAVE BEEN FULLY COMPLIED WITH.

A F F I D A V I T \*of Brandt Drilling Co., Inc.

Timothy E. Brandt, Vice Pres. & Gen.Mgr, \*being of lawful age, hereby certifies that:

I am the Affiant, and I am familiar with the contents of the foregoing Affidavit.

8-1-1E

Handwritten initials


(Office Use Only)  
KCC \_\_\_\_\_  
KGS   
SWD/REP \_\_\_\_\_  
PLG. \_\_\_\_\_  
NGPA \_\_\_\_\_

ACO-1 Well History

Side TWO OPERATOR The Dallas Group, Inc. LEASE NAME Rift #1-83 Ltd. (E)  
SEC 8 TWP 1S RGE 1E (M)  
 WELL NO 33

FILL IN WELL INFORMATION AS REQUIRED:

Show all important zones of porosity and contents thereof; cored intervals, and all drill-stem tests, including depth interval tested, cushion used, time tool open, flowing and shut-in pressures, and recoveries.

Show Geological markers, logs run, or other Descriptive information.

Formation description, contents, etc. Top Bottom Name Depth

_____ Check if no Drill Stem Tests Run. _____ Check if samples sent Geological Survey.				
Soil & Sand	0	185		
Shale & Shells	185	305		
Shale	305	580		
Lime & Shale	580	710		
Shale & Shells	710	1050		
Lime	1050	1270		
Shale & Lime	1270	1580		
Chert & Shale	1580	2050		
Lime & Shale	2050	2700		
Lime	2700	3010		
Lime & Shale	3010	3445		
Rotary Total Depth		3445		

If additional space is needed use Page 2

Report of all strings set — surface, intermediate, production, etc.

CASING RECORD (New) or (Used)

Purpose of string	Size hole drilled	Size casing set (in O.D.)	Weight lbs/ft.	Setting depth	Type cement	Socks	Type and percent additives
Surface	12-1/4"	8-5/8"	25#	328	Common	270	2% Cal. Chloride 1/4# D-29

LINER RECORD

PERFORATION RECORD

Top, ft.	Bottom, ft.	Socks cement	Shots per ft.	Size & type	Depth interval

  

TUBING RECORD		
Size	Setting depth	Pecker set at