

WELL LOG BUREAU, KANSAS GEOLOGICAL SOCIETY
BITTING BLDG., WICHITA, KANSAS

CASING RECORD

LOCATION: NWc of the SW $\frac{1}{4}$ of the NW

SEC 51 T 20 R 11E.

10" 1450
20" 8 1-4 1662
15 1-2 6 5-8 1970
12 1-2 749 5 3-16

FARM Rice
COMPANY Ritchey and Moore.
CONTRACTOR
COMMENCED

NO. 1 COUNTY Lyon



TOTAL DEPTH 2610

SHOT QUARTS BETWEEN

CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO Ritchey & Moore.

4th Nat'l Bank Bldg. Wichita, Kansas.,
FIGURES INDICATE BOTTOM OF FORMATIONS,

ELEVATION 1266
INITIAL PRODUCTION Dry

REMARKS

Formation	Depth	Formation	Depth.
yellow clay	10	lime soft	1485
lime	15	lime hard	1490
slate blue	100	lime hard	1495
slate blue	200	lime	1520
lime	245	shale blue	1545
shale light	310	shale blue	1590
shale light	380	shale blue	1620
lime	390	lime	1638
shale light	430	shale blue	1645
shale	455	shale blue	1662
lime	490	lime	1695
shale	510	shale blue	1720
lime	530	shale blue	1750
lime	540	SMALL SHOW OIL AT 1800	
shale	555	lime	1760
lime	580	shale blue	1800
shale	600	water sand	1805 2BWPH
lime	610	shale blue	1820
shale	620	shale blue	1860 HFW
lime	630	water sand	1890
lime	640	shale blue	1900
shale	730	lime	1915
shale	740	shale blue	1970
lime	750	shale blue	2007
shale	760	water sand	2010
lime	780	2 B.W. P. Hr	
lime	790	shale dark	2013
shale black	795	red rock	2016
lime	800	shale light	2050
shale brown	810	shale light	2060
lime	825	shale dark	2145
lime	855	shale dark	2167 - m
shale brown	875	lime	2200
shale white	940	lime	2245
shale blue	960	lime	2285
lime	965	lime	2310
shale white	1030	water sand	2320
lime hard	1110	sandy lime	2345
lime soft	1135 2 B.W.	lime hard	2370
lime hard	1220 Per Hr.	lime hard	2395
lime hard	1280	lime hard	2420
lime hard	1325 2BW	lime hard	2445
lime soft	1335	lime hard	2475
lime hard	1360	lime	2490 - k
lime	1380	shale	2520
red rock	1390	shale light	2540
shale	1395	shale light	2560
lime	1440	shale light	2585
lime hard	1475 3BW	lime	2600
		lime	2605 HFW
		water sand	2610 T.D.