

Company - THE TEXAS COMPANY
Farm - A. N. Smith (Dove) No. 2-W

SEC. 10 T. 21 R. 22E
NE SW SE NW
Approx. 565' fr S1 & 400' fr
W1 E $\frac{1}{2}$ NW $\frac{1}{4}$
County. Linn

Total Depth. 530 $\frac{1}{2}$ ' PB 527'
Comm. 2-12-47 Comp. 12-4-47
Shot or Treated. Shot SNG 28" 499' to 527'
Contractor. Shewmaker
Issued. 9-25-48

KANSAS



CASING:
8-5/8" 20'
7" 456' P.

Elevation. _____

Production. Water Input

Figures Indicate Bottom of Formations.

soil	2
clay	10
gravel	12
shale	19
lime	60
shale	66
lime	83
shale drk	90
lime	93
shale drk	97
lime	107
lime shells	110
lime	112
shale	268
lime	275
shale	286
lime	289
shale	291
lime	299
shale	350
lime	362
shale	364
lime shells	365
shale	367
lime	369
shale	375
lime	388
shale	406
lime	414
shale	418
lime	421
shale	429
lime	437
shale	439
lime	442
shale blk	450
lime	455
shale	471 $\frac{1}{2}$
shale sdy gy	476
sand brwn & shale	481
lost core	489
hrd brwn sand	491
shale sdy	494
sand hrd brwn	497-5
sand hrd blk	500-5
sand brwn	501-8
sand blk	502
sand brwn	508-5
sand brwn sft	511-5
sand brwn sft	523
sand brwn hrd	524
sandbrwn sft	529
shale blk	530-5
Total Depth	

Plugged back to 527'

Cored, 471-530 $\frac{1}{2}$
Top Squirrel Sand 471'
Packer 494'