19-21-3E


WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock, Wichita, Kansas

Company. ANDERSON PRICHARD OIL CORPORATION
Farm. Slocombe No. 5

SEC. 19 T. 21 R. 3E
NW SW NE

Total Depth. 2876'
Comm. 1-6-57 Comp. 1-13-57
Shot or Treated.
Contractor. Glenn W. Peel
Issued. 2-16-57

County Marion KANSAS



Elevation. 1445' RB

Production. 8 hr State; 141 BOPD no wtr.

CASING:
8 5/8" @ 122' cem.
5 1/2" @ 2875' cem.

Figures Indicate Bottom of Formations.

surface soil	70	
lime	330	
lime & shale	670	
shale	1300	
lime & shale	1780	
sand & shale	1975	
lime & shale	2210	
lime	2570	
lime & chert	2690	
lime	2705	
shale & lime	2735	
shale	2836	
Hard lime	2864	
shale	2876	RTD
Total Depth		

TOPS	SAMPLE	SCHLUMBERGER
Lansing		2014
Mississippi	2584	2575
Kinderhook	2697	2689
Hunton	2835	2837

Swb & bailed hole dry to 2841. CO to 2871
Perf. 2860-66 (Schl meas.) w/ 4 sh ch per ft.
2 hrs. filled up 2250' wtr.
3 " " " 2350' wtr. & 100' oil
Ran 2" tbg w/squeeze tool. Set pkr 2850. Prep.
to squeeze w/150 sx Squeezed perfs.
Perf. 2838-44 w/4 sh ch per ft.
15 min. filled up 2150' oil, no wtr.
45 min. " " to surface w/oil, no wtr.
Swbd 137 BO no wtr in 14 hrs. POP