

WELL LOG BUREAU—KANSAS GEOLOGICAL SOCIETY
508 East Murdock,


Wichita, Kansas 14-22-11E

Company- CITIES SERVICE OIL CO.
Farm- Madison Unit "B" No. 1-S

SEC. 14 T. 22 R. 11E
NW NW NE

Total Depth. 2900' RTD
Comm. 11-10-52 Comp. 11-30-52
Shot or Treated.
Contractor. Bradley & Tickel Drlg. Co.
Issued. 9-4-54

County Greenwood
KANSAS



Elevation. 1212' RTB (4' above C)

Production. Wtr. supply well.

CASING:

13" 61' w/45 sx cem.
8 5/8" 2537' w/425 sx cem.

Figures indicate Bottom of Formations.

soil	2	2465-66'	S.S.O.
lime	15	2466-82'	N.S.O.
shale	35	2482-84'	V.S.S.O.
lime	38	2484-90'	N.S.O.
shale	42		
lime	48	Top Chert-sand	2490
shale	54	2490-2519'	N.S.O.
lime	57		
shale	61	Top Arbuckle Dol.	2520
shale-shells	230	2573-2900	N.S.O.
shale-lime	460		
shale-lime	810	Pen in Arb. 380'	
shale-sand	898		
shale-lime	1005	Drill In:	
lime	1144	Drld. Cem. plug & C.O. to 2900' TD	
lime-shale	1210		
lime	1248	Steel Line Measurement:	
lime-shale	1530	531-531'	1941-1943'
lime	1572	759-759'	2380-2380'
lime-shale	1666	1144-1144'	2538-2539'
shale	1750	1786-1786'	2681-2682'
lime-shale	1847	1838-1889'	2900-2900'
shale-sand	1886		
sand	1889		
sand-shale	1939		
sand	1941		
sand-shale	1948		
shale-sand	1952		
shale	1955		
lime-shale	2036		
lime	2040		
sand-chert-lime	2064		
lime-chert	2090		
lime	2206		
lime-chert	2376		
lime-shale	2423		
shale	2437		
lime stks-shale	2484		
shale-chert-sand	2500		
lime-shale-chert	2539		
lime	2541		
lime-cherty	2569		
lime-chert	2623		
lime	2680		
lime-chert	2696		
lime	2900	RTD	
Total Depth			

TOPS:

Top Bartlesville Ss. 1854
1854-98' S.S.O. Base 1944'
1898-1940'- N.S.O.
1941-43' F.S.O.
1943-44' S.S.O.

Top Miss Sec. (chert) 2035
2035-2392 N.S.O. Base 2392'

Top Kinderhook Sh. 2392
2392-2465' N.S.O. Base 2490'