

Location NW c NE/4


Sec. 11 T. 22 R. 10E.

330' fr NL 330' fr WL W/2 NE/4

County- Greenwood.

Casing Record

10" 1178 Farm- O. H. Green No. 3  
 20" 8" 1724 Company- Phillips Petr. Co.  
 15 $\frac{1}{2}$ " 65/8" 2107 Contr:- Harry Gore.  
 12 $\frac{1}{2}$ " 607 53/16" Comm:- 12/3/1928. Corp:- 12/29/1928.  
 Total Depth 2136'. Shot 150 Quarts Between 2096-2130.  
 Correspondence Regarding This Well Should Be Referred to



Elevation

Initial Production 238 bbls.

Figures Indicate Bottom of Formations.

Date Issued. 2/16/1929.

Formation	Depth	Formation	Depth.
soil blk soft	3	shale grey soft	1365
clay yellow soft	20	lime white hard	1374
lime white hard	24	shale grey soft	1415
shale grey soft	94	lime grey hard	1435
lime white hard	104	shale grey soft	1465
shale grey soft	135	2BWPBR 1525-1535	
lime white hard	150	lime white hard	1535
shale grey soft	175	shale blue soft	1542
lime white hard	195	lime white hard	1592
shale grey soft	215	shale grey soft	1706
lime white hard	230	8 $\frac{1}{2}$ " casing 1706- 6"	
shale blue soft	242	lime white hard	1715
lime white hard	250	shale white soft	1735
shale grey soft	256	lime white hard	1750
lime white hard	260	shale grey soft	1802
shale blue soft	268	lime white hard	1810
lime white hard	310	shale grey soft	1820
slat $\frac{1}{2}$ blue soft	335	lime grey hard	1835
shale grey soft	341	shale blue soft	1855
lime white hard	398	lime grey hard	1875
shale grey soft	404	shale grey soft	1917
lime blue hard	408	lime grey hard	1922
shale blue soft	423	shale dark soft	1950
lime blue hard 1BWPHR 450	490	lime white hard	1955
shale grey soft	531	shale grey soft	2058
lime white hard	552	shale blk soft	2077
shale grey soft	560	6-5/8 Casg at 2081	
lime wh hard 2BW 570	570	shale light soft SLM	2081
shale sdy blue soft	595	top of sand gr soft	2081
shale grey soft	613	1st oil light soft	2095
lime grey hard 12 $\frac{1}{2}$ " csg 610	620	more oil light soft	2109-32
shale grey soft	630	Total depth light soft	2136
shale blue soft	635		
lime blue hard	643		
shale blue soft	655		
lime white hard	673		
shale blk soft	675		
brkn lime wh med hard	715		
shale gr soft	725		
lime white hard	740		
shale gr soft	792		
lime white hard	799		
shale grey soft	818		
lime grey hard	842		
shale blk soft	848		
lime wh hard	853		
shale grey soft	860		
lime white hard	880		
shale grey soft	920		
shale grey soft	930		
shale dark soft	1030		
sdv lime dark soft	1035		
lime white hard	1075		
shale grey soft	1075		
3BW 1075-1085			
sand grey soft	1085		
shale grey soft	1175		
10" casing 1175-10"			
lime white hard	1180		
shale grey soft	1184		
1BWPHR 1200			
lime white hard	1290		

SAND RECORD.

Top of sand	2081
top of 1st oil	2095
bottom oil sand	2130
T.D.	2136
P.T.D.	2136
sand light grey sft true	