

27-22-13E

WELL LOG BUREAU, KANSAS GEOLOGICAL SOCIETY
BITTING BUILDING, WICHITA, KANSAS

CASING RECORD


LOCATION

SEC 27 T 22 R 13E

20" 10" 1003 FARM **Horris**
8 1-4 1006 COMPANY **Braden Brothers & Co.**
15 1-2 6 5-8 236 CONTRACTOR
12 1-2 730 5 3-16 COMMENCED

NO. 3 COUNTY **Greenwood.**

COMPLETED **May 1, 1924.**



TOTAL DEPTH **1848**

SHOT

QUARTS BETWEEN

CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO

FIGURES INDICATE BOTTOM OF FORMATIONS

ELEVATION

INITIAL PRODUCTION **1st 24 hours 15 bb**

REMARKS

Formation	Depth	Formation	Depth.
gravel	12	slate	1340
shale	75	lime	1348
lime	106	slate	1358
shale	140	lime	1378
lime	150	shale	1395
red rock	170	sand	1405
shale	200	8 Bailers water per hour	
lime	210	lime	1455
shale	220	shale	1475
lime	260	lime	1488
shale little water 300 ft	300	shale	1500
lime	305	shale	1548
shale	370	lime	1550
lime	380	add 8ft later set 1597 ft 8" casing	
slate	400	shale	1597
lime	465	shale	1710
shale	665	lime	1775
lime 10 B. W. 680-690	685	hole reduced to 1813	
sand	695	shale	1833
lime	706	sand	1848
shale	734	lime	1848T.D.
lime water 745 HF	790		
shale	800		
lime water 960-980	1018		
shale	1028		
red rock	1033		
lime	1038		
shale	1068		
lime	1168		
slate	1300		
lime	1395		

Comm.
Comp.
i. p. 1st. 24 hrs. 15 bbls.
loc.

27-22-13E
Norris # 3
Greenwood Co., Ks.

PLOTTED

graves	12
shale	75
lime	105
shale	140
lime	150
red rock	170
shale	200
lime	210
shale	220
lime	260
shale little wtr.	300
lime	305
shale	370
lime	380
slate	400
lime	465
shale	665
lime	685
LOBW 680 to 690	
sand	695
lime	705
shale	734
lime wtr. 745 hole	790
shale	800
lime W. 960 - 980	1018
shale	1028
red rock	1033
lime	1038
shale	1058
lime	1188
slate	1300
lime	1305
slate	1340
lime	1345
slate	1350
lime	1375
shale	1395
sand 8BW hr.	1405
lime	1455
shale	1475
lime	1485
shale	1500
shale	1545
lime	1550

shale
shale
lime
shale
sand
lime

1597
1710
1775
1835
1845
1848 T. D.

RETURN TO GYPSY OIL CO.