

Location. SEc SE

Sec 15 T. 22 R. 13E.


(SE SE SE SE) - SE CORNER SE

Casing Record.

County Greenwood. OCT 8

1932

20" 10" 719 Farm. H. F. Povemire No. 5
 15 1/2" 8 1/2" 1037 Company. Aikman and Sons.
 12 3/4" 65/8" 1820 Contr. W.F. Braden.
 12 3/4" 53/16" Comm. 6-13-32 Comp. 7-5-32
 Total Depth. 1876 Shot Quarts Between.
 Correspondence Regarding This Well Should Be Referred to.



Elevation. 1232

Figures Indicate Bottom of formations.

Initial Production.

Date Issued. 10-8-32

Est 5 B.O. 5 B W.

Formation	Depth	Formation	Depth.
soil	3	shale	1185
shale	85	lime	1190
lime	87	shale	1312
shale	90	lime	1319
lime	99	shale	1340
shale	104	lime	1348
lime	123	shale	1352
shale	140	lime	1360
lime	160	shale	1370
shale	170	lime shell	1420
lime	230	lime	1425
shale	245	slate	1428
lime	280	lime	1435
shale	289	shale	1442
lime	294	lime	1447
shale	385	slate	1460
lime	390	lime	1470
shale	403	shale	1478
lime	425	lime	1490
shale	430	shale	1530
lime	465	sand	1541
shale	647	shale	1570
lime	650	lime	1572
sand	660	shale	1575
shale	670	lime	1577
sand	685	shale	1834
shale	700	sand	1844
sand	707	oil 1 bailer an hour natural.	1870
shale	755	lime	1875
lime	785	lime brown	1876
shale	793	lime grey	1876
lime	805	water 1 bailer an hour plugged back	
shale	810	to 1874 and shut off water.	
lime	845		
shale	850	TD.	
lime	1013		
shale	1019		
lime	1024		
red rock	1032		
shale W.	1069		
lime	1150		
shale	1156		
lime	1180		