CASING RECORD

LOCATION 250' fr W.L. 910 frNL SEC 18 T 22 R 11E.

SW¼ 18-22-11E

10" FARM Clopton NO. 3 COUNTY Greenwood

Plotted L.R.

20" 8 1-4 COMPANY Mid-Continent Petroleum Corp.

15 1-2 6 5-8 CONTRACTOR

12 1-2 5 3-16 COMMENCED 5-24-25 COMPLETED 6-16-25



TOTAL DEPTH SHOT QUARTS BETWEEN

CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO

ELEVATION

FIGURES INDICATE BOTTOM OF FORMATIONS INITIAL PRODUCTION

REMARKS

Formation	Depth
soil	10
slate	20
lime	25
slate	90
lime	100
slate	130
lime	140
slate	160
slate and shell	220
lime	230
slate	240
slate	280
lime	290
slate	370
lime	385
slate	395
lime	410
slate	470
lime	490
slate	495
lime	530
slate	540
lime	545
slate	570
lime	580
slate blk	585
lime	595
slate	600
lime	615
slate	608
lime	615
slate blk	630
lime	645
slate	670
lime	700
slate	710
lime	715
slate	720
lime	730
slate	760
lime	820
slate blk	825
lime	830
slate	900
lime	905
slate	1060
lime	1065
sand brown HFW	1085

Formation	Depth.
slate brown	1090
sand brown wtr	1120
sdy slate brown	1155
lime	1185
slate blk	1190
lime	1205
slate	1210
lime 2BW 1225	1275
slate	1385 10BW 1395
oswego lime	1515
slate	1525
lime	1550
slate	1553
lime	1558
slate and shells	1570
slate	1690
lime 10BW 1730	1730
slate	1740
sand brown	1750
slate	1760
[illegible] lime	1767
slate	1785
lime	1795
slate	1810
lime	1825
slate	1830
lime	1835
[illegible] slate	1855
lime	1865
slate	1870
lime	1875
slate	1915
lime	1920
slate	1960
lime	1965
slate	2055
slate blk	2068
lime	2070
slate blk	2078
sdy slate	[illegible] 2093
sand brown	2123
slate blk TD	2125

WELL RECORD

J. D. Clopton Lease, Well # 3

SW¼ Sec 18-22-11 Greenwood Co. Kans. 250' from W line & 910' from N line
Drilling commenced May 24, 1925. Drilling completed June 16th, 1925.
Well drilled by Patton Drilling Company

FORMATION	FROM	TO	REMARKS
Soil, soft	0	10	
Slate, blue soft	10	20	
Lime, white hard	20	25	
Slate, blue soft	25	90	
Lime, white hard	90	100	
Slate, white soft	100	130	
Lime, white hard	130	140	
Slate, blue soft	140	160	
Slate & Shell, light hard	160	220	
Lime, white hard	220	230	
Slate, white soft	230	240	
Slate, blue soft	240	280	
Lime, white hard	280	290	
Slate, white soft	290	370	
Lime, white hard	370	385	
Slate, blue soft	385	395	
Lime, white hard	395	410	
Slate, blue soft	410	470	
Lime, white hard	470	490	
Slate, blue soft	490	495	
Lime, white hard	495	530	
Slate, blue soft	530	540	
Lime, white hard	540	545	
Slate, white soft	545	570	
Lime, white hard	570	580	
Slate, black soft	580	585	
Lime, white hard	585	595	
Slate, blue soft	595	600	
Lime, white hard	600	605	
Slate, blue soft	605	608	
Lime, white hard	608	615	12½" Set @ 614'
Slate, black soft	615	630	
Lime, white hard	630	645	
Slate, blue soft	645	670	
Lime, white hard	670	700	
Slate, blue soft	700	710	
Lime, white hard	710	715	
Slate, blue soft	715	720	
Lime, white hard	720	730	
Slate, blue soft	730	760	
Lime, white hard	760	820	
Slate, black soft	820	825	
Lime, white hard	825	830	
Slate, blue soft	830	900	
Lime, white hard	900	905	
Slate, blue soft	905	1060	
Lime, white hard	1060	1065	
Sand, brown soft	1065	1085	H F W
Slate, brown soft	1085	1090	
Sand, brown soft	1090	1120	Water
Sandy slate, brown soft	1120	1155	10" Set @ 1155'
Lime, white hard	1155	1185	
Slate, black soft	1185	1190	
Lime, white hard	1190	1205	
Slate, bray soft	1205	1210	
Lime, white hard	1210	1275	2 Blrs water @ 1225'
Slate, blue soft	1275	1350	
Slate, gray soft	1350	1385	
Oswego lime, white hard	1385-	1515	10 blrs water @ 1395'
Slate, dark soft	1515	1525	
Lime, white hard	1525	1550	

WELL RECORD

J. D. Clopton Well #3 Page 2

Slate, dark soft	1550	1553	
Lime, white hard	1553	1558	
Slate & shells, light soft	1558	1570	
Slate, blue soft	1570	1690	
Lime, white hard	1690	1730	10 blrs water @ 1730'
Slate, white soft	1730	1740	
Sand, brown soft	1740	1750	
Slate, gray soft	1750	1760	
Lime, white hard	1760	1767	8¼ Set @ 1764' SIM
Slate, blue soft	1767	1785	
Lime, white hard	1785	1795	
Slate, blue soft	1795	1810	
Lime, white hard	1810	1825	
Slate, blue soft	1825	1830	
Lime, white hard	1830	1835	
Slate, blue soft	1835	1855	
Lime, white hard	1855	1865	
Slate, blue soft	1865	1870	
Lime, white hard	1870	1875	
Slate, blue soft	1875	1915	
Lime, white hard	1915	1920	
Slate, blue soft	1920	1960	
Lime, white hard	1960	1965	
Slate, blue soft	1965	2055	
Slate, black soft	2055	2068	
Lime, gray hard	2068	2070	
Slate, black soft	2070	2078	
Sandy slate, light soft	2078	2093	6-5/8" set @ 2080' SIM
Sand, brown, medium	2093	2123	
Slate, black soft	2123	2125	6-5/8" lowered to 2086'
Total Depth	2125		

CASING RECORD

SIZE		PULLED	LEFT IN
12½"	614'	614'	
10"	1155'	1155'	
8¼"	1764'		1764'
6-5/8"	2086'		2086'