


WELL LOG BUREAU, KANSAS GEOLOGICAL SOCIETY  
BITTING BLDG., WICHITA, KANSAS

CASING RECORD

LOCATION 990 fr S.L. 990 fr E.L. SW<sup>1</sup>/<sub>4</sub>

SEC 20 T 22 R 10E

20' 10" 1402 FARM J. A. Browning NO. 31 COUNTY Greenwood.  
 15 1-2 90 8 1-4 2046 COMPANY Sinclair Oil and Gas Co.  
 12 1-2 795 6 5-8 2257 CONTRACTOR Elliott & Cassell.  
 5 3-16 COMMENCED 11-12-25 COMPLETED 12-5-25  
 TOTAL DEPTH 2326 SHOT QUARTS BETWEEN



CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO Sinclair Oil & Gas Co.  
 Tulsa, Oklahoma. ELEVATION

FIGURES INDICATE BOTTOM OF FORMATIONS.  
 REMARKS

INITIAL PRODUCTION 200 bbls.

Formation	Depth	Formation	Depth.
soil	8	lime	905
lime	40	slate	915
slate	5 bailers water 45	lime	925
sandy lime	at 55 ft 55	slate	945
slate	90	lime	970
lime	105	slate	1015
slate	110	lime	1025
lime	120	slate	1040
slate	130	lime	1070
lime	140	slate	1075
slate	185	lime	1090
lime	205	slate	1140
slate	310	S. lime	1165
sandy lime	325	6 Bailers water per hour	1140-,,65
8 bailers of water from	310-325	slate	1245
slate	340	lime	1250
lime	355	water sand	1325
slate	370	MFV at 1290	
lime	375	slate	1360
slate	380	sand	1400
lime	390	lime	1500
slate	450	slate	1605
lime	460	lime	1810
slate	490	slate	1925
lime	510	lime	1935
slate	535	slate	1955
lime	540	lime	1965
slate	575	slate	2015
lime	590	lime	2020
slate	630	slate	2050
lime	655	slate	2060
slate	710	lime	2070
lime	725	slate	2080
slate	745	lime	2085
lime	760	slate	2175
slate	785	lime	2180
3 Bailers water at 770		slate	2257
lime	800	pay sand	2326
slate	815		
lime	835		
slate	860		
lime	870		
slate	885		