

26-22-24E


Company

Sec. 26 T. 22 R. 24
Loc. ENE

Farm Lewis Heilman No. 1

County Linn

Total Depth 534
Comm. Comp.
Shot or Treated
Contractor
Issued



Casing
20 in. 10 in.
15 1-2 8 1-4
12 1-2 6 5-8
13 3-8 5 3-16

Elevation
Production

Figures Indicate Bottom of Formation

soil	1		4 white shale	309
clay yellow	15		9 shale blue	318
3 sand stone	18	Kn	FS 12 lime	330 little gas
20 shale blue	38		5 slate black	335
20 lime	58		4 lime	339
2 shale dark	60	water	6 shale blue	345
8 lime	68		SP 5 sand oil show	350
30 shale	98		25 shale blue	375
7 lime shells	105		2 lime	377
29 shale light	139		13 shale blue	390
9 lime	143	✓	5 black shale	395
25 light shale	168		40 light shale	435
18 lime	186	A	And 4 lime black	439
9 sand show oil	195	Band	3 slate black	442 little gas
43 shale blue	238		3 lime black	445
19 lime	257	Pow	27 shale white	472
5 shale dark	262	water	16 shale blue	488
4 lime	266		2 lime	490
36 shale blue	290		30 light shale	520
10 sand	300	Perm	5 broken sand	525
5 lime	305		UPV BV 9 sand water	534 TD Dry hole

Lewis Hulman Farm
Inland Mtge Corp. S.W. corner

Started Feb. 3, 1935

Reynolds Bros.

E 1/2 NE 1/4 of Sec. 26-22-24

1	Soil	1	
14	Yellow clay	15	
3	Sand stone	18	
20	Shale blue	38	
20	lime	58	
2	Shale dark	60	water
8	lime	68	
30	Shale blue	98	
7	lime shells	105	
29	Shale light	134	
9	lime	143	
25	light shale	168	
18	lime	186	
4	Sand oil show.	195	
43	Shale blue	238	
19	lime	257	
5	Shale dark	262	water
4	lime	266	
24	Shale blue	290	
10	Sand	300	
5	lime	305	
4	White shale	309	
9	" blue	318	
12	lime	330	little gas
5	Slate black	335	
4	lime	339	
6	Shale blue	345	
5	Sand oil show	350	
25	Shale blue	375	
2	lime	377	
13	Shale blue	390	
5	black shale	395	
40	light	435	
4	lime black	439	
3	Slate "	442	little gas
3	lime "	445	
27	shale white	472	
16	" blue	488	
2	lime	490	
30	light shale	520	
5	broken sand	525	
9	sand water	534	

Reduced 6 1/4 @ 200'

Dry Hole plugged with plaster

Feb 10 - 1935.

Hellman & Sackett, Dallas Evans, Hoffman Smith