

10" 440 FARM Al Fankhauser
 20" 8 1-4 1340 COMPANY T. K. Simmons
 15 1-2 6 5-8 1802 CONTRACTOR Frank Fesenyer
 12 1-2 5 3-16 COMMENCED

28-22-12 E
 NO. 1 COUNTY Greenwood

COMPLETED Apr. 30, 1926



TOTAL DEPTH 1955' SLM SHOT QUARTS BETWEEN

CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO

ELEVATION 1098
 INITIAL PRODUCTION D. & A.

FIGURES INDICATE BOTTOM OF FORMATIONS.
 REMARKS

Formation	Depth	Formation	Depth
soil, soft	10	shale light soft	1760
lime white hard	25	shale dark soft	1785
mud white soft	35	shale sandy light soft	1800
lime white hard	45	(Set 6 5/8" csg. at 1 02')	
shale blue soft	120	shale drk soft	1825
lime white hard	145	sand Bartlesville soft	1830
shale light soft	260	shale light soft	1870
lime grey hard	270	lime Miss. hard	1940
shale blue soft	290	water sand light hard	1955
lime white hard	300		
shale blue soft	350	Total Depth SLM (HFW)	1955'
lime white hard	360		
shale light soft	440		
(Set 10" csg. at 440')			
lime white hard	470		
shale blue soft	510		
lime white hard	540		
shale blue soft	705		
(9 Bailers at 715')			
lime white hard	730		
shale blue soft	760		
sand white soft	780		
water sand white soft (HFW)	790		
lime white hard	797		
shale blue soft	803		
lime white hard	945		
shale light	1035		
lime white hard	1090		
shale blue soft	1105		
lime white hard	1230		
shale blue soft	1240		
lime white hard	1250		
shale blue soft	1390		
(Set 8 1/2" at 1340')			
lime white hard	1400		
shale light soft	1520		
shale dark hard	1560		