


330 from NL

Miller

30-22-11E

10" 1148 FARM W. G. Coffman NO. 1 COUNTY Greenwood.
 20" 8 1-4 1847 COMPANY Phillips Petroleum Co.,
 15 1-2 6 5-8 2083 CONTRACTOR Long Drilling Co.
 12 1-2 609 5 3-16 COMMENCED Aug 16, 1925. COMPLETED Sept 5, 1925.
 TOTAL DEPTH 2105 SHOT 140 QUARTS BETWEEN 2073-2103



CORRESPONDENCE REGARDING THIS WELL SHOULD BE REFERRED TO Phillips Pet. Co.
 Bartlesville, Okla. ELEVATION 1238 Gr.

FIGURES INDICATE BOTTOM OF FORMATIONS.
 REMARKS

INITIAL PRODUCTION 50 bbls.
 after shot 200 bbls.

Formation	Depth	Formation	Depth.
surface dark soft	15	sand light soft	1050
shale dark soft	60	shale dark soft	1085
shale dark soft	100	sand white soft	1125
lime light hard	110	shale white soft	1137
shale blue soft	120	sand white soft	1140
lime light hard	130	10" 1140	
shale light soft	160	lime white hard	1153
lime light hard	175	shale blue soft	1156
shale light soft	190	lime light hard	1210
shale light soft	200	lime light hard	1280
lime light hard	230	LBW 1260	
shale light soft	245	slate light soft	1395
shale blue soft	290	1 BW 1260	
lime light hard	305	slate light soft	1395
shale dark soft	330	lime light hard	1410
lime light hard	342	shale light soft	1420
shale light soft	345	lime light hard Oswego	1475
lime light hard	355	4 B.W.	
shale light soft	363	sand water light soft	1482
shale blue soft	375	lime light hard	1560
shale blue soft	445	shale dark soft	1700 Caving.
lime light hard	475	shale light soft	1775
shale light soft	515	lime light hard	1795
lime light hard	525	shale dark soft	1805
shale light soft	550	8 BW	
lime light hard	570	lime dark hard	1809
sand light soft	585 10BW	shale dark soft	1823 8" Csg
shale light soft $\frac{1}{2}$	590	lime light hard	1828
lime light hard	600 12 $\frac{1}{2}$ -605	shale dark soft	1833
lime light hard	625	lime light hard	1852
shale light soft	630	shale dark soft	2040
shale light soft	645	shale dark soft	2050
lime light hard	665	Bartlesville sand	
shale light soft	685	light	2103
lime light hard	700	shale blue soft	2105 T.D.
shale light soft	745	6" 2053	
lime light hard	755		
shale light hard	815	REMARKS:- Brown sand,	
1 B. W. 790		top very hard to 2073,	
shale dark soft	835	from 2073 to 2103 soft.	
lime light hard	845		
shale light soft	850		
shale light soft	853		
lime light hard	855		
shale light soft	875		
lime light hard	877		
shale light soft	1010		
lime light hard	1015 HFW		