STEELE #1
Owner: T. K. Simmons
Contractor: The Shull Drg Co.

Location SE/c NE/4 Sec. 32-22-12
Greenwood County, Kansas.
Spudded on October 15th, 1929.
Completed drilling Nov. 1st, 1929.

RECORD OF FORMATIONS

Soil		5	5
Lime		8	13
Slate		17	30
Shale	gray	45	75
Lime	white	45	120
Shale	blue	10	130
Lime	white	15	145
Shale	gray	25	170
Lime	white	20	190
Slate	light	10	200
Lime	light	15	215
Slate	light	25	240
Lime	white	15	255
Shale	gray	20	275
Lime	white	15	290
Slate	light	100	390
Lime	white	10	400
Shale	light	15	415
(Set 12½" casing at 414)			
Lime	light	25	440
Shale	blue	10	450
Lime	white	15	465
Slate	light	220	685
Lime	light	10	695
(6 B W 605--705 ft)			
Sand	light	65	760
(H F W 740--760 ft)			
Lime	light	5	765
Slate	dark	5	770
Lime	light	20	790
Lime	light	5	795
(Set 10" casing at 794)			
Shale	light	30	825
Lime	light	105	930
(1 B W 850--860 ft)			
Shale	light	90	1020
Lime	light	55	1075
Shale	light	10	1085
Lime	light	60	1145
Shale	light	5	1150
Lime	light	45	1195
Slate	dark	5	1200
Lime	light	5	1205
Slate	light	120	1325
Lime	light	10	1335
Slate	light	25	1360
Lime	light	5	1365
(Set 8¼" casing at 1365 ft)			
Lime	light	5	1370
Shale	light	60	1430
Lime	light	45	1475
(2 B W 1470--1475 ft)			
Shale	light	50	1525
Slate	dark	70	1595
Shale	light	100	1695 ft
Slate	PINK	5	1700
Slate	light (cave)	35	1735
Shale	gray	25	1760
Shale	dark (cave)	15	1775
(Set 6-5/8" casing at 1775)			
Shale	dark	15	1790
Slate	dark	55	1845
Lime	MISS White	95	1940
(2 B W 1845--1850 ft)			
Total depth			1940

Casing record:

12½"	set	414 ft
10"	"	794 ft
8¼"	"	1365 ft
6-5/8"	"	1775 ft

State of Kansas. Greenwood County:

I hereby certify that the above and foregoing is a true and correct copy of log of Steele #1 drilled by T.K.Simmons in the SE/c of NE/4 of section 32-22-12 Greenwood County, to the best of my knowledge and belief.

HH Harry Horn
Superintendent
for T. K. Simmons.

Subscribed and sworn to before me this 5th day of November, 1929.

John Daugherty
Notary Public.

My Commission expires May 18th, 1933.